

Integrated Controls Package

Integrated control solutions are provided by the heat pump manufacturers for listing on the ICQPL. This is meant to ensure solutions are approved by the manufacturer and do not Invalidate the manufacturer warranty for equipment installed.

To qualify, the IC must switch from heat pumps as the primary to the combustion system as the secondary. The changeover must be done automatically based on a preset outdoor temperature. The outdoor temperature can be determined by a local outdoor temperature sensor or via Wi-Fi weather data. For example, all ductless mini split heads in given heating zone must switch to existing boiler via IC communication with no user interaction.

Dual Fuel Thermostat

Dual fuel thermostats must be capable of doing at least two stages of heat and two stages of cooling and able to automate the changeover between the primary and secondary heat source based on an outdoor temperature. The temperature sensing can be via Wi-Fi weather data or via a local hard wired temperature sensor then it would be approved for the ICQPL.

Integrated Controls Package

Manufacturer	Model Name	Model #	24v (Y/N)	Communicating (Y/N)	WiFi Enabled (Y/N)	Notes
Any IR Controlled Mini-split + Flair	Puck Pro	FLAIRPUCK001P	N	N	Y	Compatible Mini Split Brands and Compatible Smart Thermostats Listed at: flair.co/integrated-controls Flair Puck Pro is required for each mini split head unit and the Flair system must be digitally cloud integrated with one of the following thermostats: Honeywell: T6 Pro TH6320WF2003, T10 THX321WFS2001W, Round RCH9310WF ecobee: EB-STATE5-01, EB-STATE4-01, EB-STATE3-02, EB-ecobee3-01, EB-STATE3L-01, EB-STAT-02, EB-SMARTSI-01, EB-EMSSI-01 Nest: Third Gen Compatible with all Amana Heating and Air conditioning brand communicating equipment
Amana Heating and Air Conditioning	Amana Smart Thermostat	ATST-CWE-BL-A	N	Y	Y	
Bosch	24V Interface	BMS-DRY-XXX	Y	Y	Y*	Requires one 24V Interface Kit, One Third Party Thermostat and double pole double throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the thermostat selected.
Bosch (Airzone)	Aidoo Pro	AZAI6WSPMD1	N	Y	Y	Compatible with all ducted and non-ducted units that have X-Y-E wiring. It can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the Aidoo Pro can be used on its own for the integrated control as it has a Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native Mitsubishi controls, switchover can be done based off of outdoor temperature through the app.
Carrier	24V Interface	KSAIC0301230	Y	Y	Y*	Requires one 24V Interface Kit, one Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the Thermostat selected.
Cielo WiGle Inc.	Cielo Breez Plus (Smart AC controller for any brand ductless systems)	BP101WA	Y	N	Y	The integrated control solution is based on Cielo's AWS Cloud platform called 'Cielo Linked'. It requires a Cielo Breez Plus smart AC controller (for ductless systems) and a Cielo Smart thermostat for the conventional ducted HVAC system (2H, 2C). No extra hardware or wiring is needed. Both Cielo Breez Plus and Cielo Smart Thermostat are connected through Cielo Linked (cloud platform). Cielo Home App is required to link the devices. Cielo Breez Plus can be powered through a 5V adapter or can be hardwired to 24V. Cielo Smart thermostat is powered through standard 24V wiring. Cielo Linked enables the interplay of connected ductless systems and conventional ducted HVAC system. After powering up the Cielo Breez Plus and Cielo Smart
Cielo WiGle Inc.	Cielo Breez Max (Smart AC controller for any brand ductless systems)	BM101WA (Black Color Variant) BM102WA (White Color Variant)	Y	N	Y	The integrated control solution is based on Cielo's AWS Cloud platform called 'Cielo Linked'. It requires a Cielo Breez MAX smart AC controller (for ductless systems) and a Cielo Smart thermostat for the conventional HVAC system (2H, 2C). No extra hardware or wiring is needed. Both Cielo Breez MAX and Cielo Smart Thermostat are connected through Cielo Linked (cloud platform). Cielo Home App is required to link the devices. Cielo Breez MAX can be powered through a 5V adapter or can be hardwired to 24V. Cielo Smart thermostat is powered through standard 24V wiring. Cielo Linked enables the interplay of connected ductless systems and conventional ducted HVAC system. After powering up the Cielo Breez MAX and Cielo Smart
Cielo WiGle Inc.	Cielo Smart Thermostat ECO	TE101WA (White Color Variant), TE102WA (Black Color Variant)	Y	N	Y	Cielo Smart Thermostat Eco supports Conventional Systems for up to 2 stages of Heating & 2 stages of Cooling. For Heat Pumps it supports up to 4 Stages of Heating and 2 Stages of Cooling. Cielo Smart Thermostat Eco fetches outdoor temperatures data from cloud and makes decisions based on that data for switching between Heat Pump and Aux heat source (dual fuel systems). In addition, the Cielo Smart Thermostat Eco can also be linked to Cielo Breez Max and/or Cielo Breez PLUS (Cielo's smart thermostats for mini splits) using Cielo Linked (our cloud-based platform to switch between fossil fuel-based systems and mini splits). Cielo Smart Thermostat Eco stores projected temperature data for next 72 hours to ensure its smooth decision-making
CMNA ICP-MIDEA	24V Interface	KSAIC0401230	Y	Y	Y*	Requires one 24V Interface Kit, one Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the Thermostat selected.
Cooper&Hunter	IFTTT	WIFI Module CH-WIFI01M & Smartport	N	Y	Y	IFTTT App connects Cooper&Hunter with IFTTT through C&H wifi remote app. Current IFTTT compatible thermostats (for additional heat source) include Ecobee, and Honeywell as of 11/1/19. For list of devices, go to www.ifttt.com/services (Environment Control & Monitoring). Integration is capable by logging compatible thermostat for additional heat source and Cooper&Hunter wifi remote app for Cooper&Hunter system into IFTTT, then creating applet to allow IFTTT to adjust primary and secondary
Daikin	One+ (Replaces ENVI)	DTST-ONE-ADA-A (Replaces DACA-TSI-1)	Y	Y	Y	Compatible with Daikin Mini-Split and Multi Split Heat Pump Products. Thermostat is provided with communication adaptor that requires 110-240 VAC power supply. Additional adaptor (KRP980B2E) required for connection to FTX NMVJU indoor
Daikin	Daikin One Lite Connected Thermostat	DTST-LTE-LA-A	N	Y	Y	Compatible with most Daikin brand mini and multi split systems, see www.daikinone.com for specific details
Daikin	Daikin One Touch Smart Thermostat	DTST-TOU-A	N	Y	Y	Compatible with all Daikin brand communicating equipment
Daikin (Airzone)	DKN Plus Interface	AZAI6WSPDKC	N	Y	Y	Compatible with Daikin Mini Splits and Daikin VRV indoor unit and allows integration of any thermostat to control the indoor unit operation. Can provide full integration via cloud API, Modbus or BACnet MSTP to control and monitor the indoor unit
EWC Controls	Ultra-Zone	BMPlus 3000	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
EWC Controls	Ultra-Zone	BMPlus 5000	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
EWC Controls	Ultra-Zone	BMPlus 7000	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
EWC Controls	Ultra-Zone	UZC-4	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems

EWC Controls	Ultra-Zone	UZC-6	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
Fujitsu	Wired Remote Controller (Touch Panel)	UTY-RNRUZ*	N	Y	N	J Series & RGLX only - The existing heat source is energized is to be operated through a 3rd party control circuit, via a 12 VDC external output signal from the indoor unit PC board.
Fujitsu	Wired or Wireless Remote Controller	Various	N	Y	N	Primary Heat lockout or secondary heat lockout based on outdoor temperature is available. See instructions for compatible equipment. The alternate heat source is operated through a 3rd party control circuit, via a 12 Vdc external outout signal from the indoor unit PC board. Primary heat lockout or secondary heat lockout based on outdoor Fujitsu General Remote Controllers (7 Items) Fujitsu General - Integrated Heating Control (Remote Controller) - Instructions
Fujitsu	N2000 (Replaces Novus N2020)	8200200130 (Replaces 8202011300)	Y	N	N	*Former controller Novus N2020* N2000 is the replacement series controller recommend by Fujitsu to be used with Airstage or Halycon Mini-Split Heat Pump System. N2000 senses outside temperature and closes the control contact when the outside temp is about the set temp. When closed, this contact will enable the Halycon to heat or cool based on the temp setting of the Halycon System; when this contact is open, it will inhibit the Heat Pump from working. The installation requires both a wiring kit and external control board supplied by Fujitsu to be added to the inside unit NOVUS N2020 Temperature Controller - Operation Manual NOVUS N2020 Temperature Controller - Operation Manual
Fujitsu	Thermostat Converter	UTY-TTRX	Y	N	N	Required installation includes a Thermostat Converter and 24 volt transformer (one UTY-TTRX can connect up to 16 indoor units), plus a dual fuel thermostat from QPL. Best as IC solution for single head, multihead, or air handler installations. Dual Fuel thermostat replaces existine central heat thermostat. Indoor units connected to each adaoer (plus dual fuel thermostat) acts as Fujitsu General - Integrated Heating Control (3rd Party Thermostat) - Instructions Third Party Thermostat Interface UTY-TTRX21 - Installation Manual
Fujitsu	WiFi Thermostat	Various	Y	Y	Y	Honeywell Wi-Fi thermostat compatible with Gas, Electric and Oil on forced air, and radiant boilers
Fujitsu	WiFi Interface (UART)	UTY-TFSXF1	N	Y	Y	IFTTT solution combining any of the (3) WiFi Interface Modules listed at left; a Honeywell dual-stage Wi-Fi thermostat with IFTTT capability, used to control the existing heat source; and the IFTTT App. Access to Fujitsu IFTTT Installation Instructions are available via the below link upon establishing a Fujitsu account Fujitsu General - Integrated Heating Control (IFTTT) - Instructions
Fujitsu	WiFi Interface (2-Wire Indoor Units)	UTY-TFSXZ2	N	Y	Y	2-Wire WiFi Module UTY-TFSXZ2 - Setting Manual
Fujitsu	WiFi Interface (3-Wire Indoor Units)	UTY-TFNXZ2	N	Y	Y	3-Wire WiFi Module UTY-TFNXZ2 - Setting Manual
Airzone (Fujitsu)	Airzone Aidoo Pro (2 wire/UART)	AZA16WSPFU2	N	Y	Y	Aidoo Pro Modules communicate with the Fujitsu system through UART connection for 2 wire units and to the control terminals for 3 wire units. The controls allow for optional simultaneous use of Fujitsu control and or 3rd party thermostat from QPL. Dual Fuel thermostat replaces existing heat thermostat. Aidoo Pro module has "AUX" heat output, can be used stand alone without additional controls to disable heat pump operation and close AUX output through "AIRZONE CLOUD" and programming FT_AZA16WSPFU2_MUL.pdf (airzonecloud.com)
Airzone (Fujitsu)	Airzone Aidoo Pro (3 wire)	AZA16WSPFUJ	N	Y	Y	Aidoo Pro Modules communicate with the Fujitsu system through UART connection for 2 wire units and to the control terminals for 3 wire units. The controls allow for optional simultaneous use of Fujitsu control and or 3rd party thermostat from QPL. Dual Fuel thermostat replaces existing heat thermostat. Aidoo Pro module has "AUX" heat output, can be used stand alone without additional controls to disable heat pump operation and close AUX output through "AIRZONE CLOUD" and programming FT_AZA16WSPFU2_MUL.pdf (airzonecloud.com)
Gree	Honeywell T6 Pro Smart	TH6320WF 2003	Y	N	Y	Requires Honeywell T6 Pro Smart (TH6320WF 2003) WiFi thermostat that turns on the secondary heat source at 40" and "Set Point" Programmable Flair Gateway (115v) WiFi 2.4Ghz Puck that will ensure the Gree mini split heat pump will be on when thermostat turns off the secondary heat. Appropriate WiFi accessibility is provided by the homeowner and not included in this
	Flair Puck	ICS001P	N	N	Y	
Haier	IFTTT	QAWF01A	N	Y	Y	Requires Ecobee Thermostat integration with Haier WiFi via IFTTT Applets. Proper understanding and installation of the Ecobee thermostat is a prerequisite.
Hisense (Airzone)	Aidoo Pro	AZA16WSPHS1	N	Y	Y	Compatible with all ducted and non-ducted units using the CN-WIRED/CN18 terminal. It can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the Aidoo Pro can be used on its own for the integrated control as it has a Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native Mitsubishi controls, switchover can be done based off of outdoor temperature. LG Option 1: PDRYCB300 + 24 V Trans. + Thermostat (1 Per IDU)
LG Electronics	Third Party Tstst Method L Model Series IDU	PDRYCB300	Y	N	Optional	
LG Electronics	Aux Heater Kit Highwall Multi	PRARS1	Y	Y	N	LG Option 2: Wall Units Multi Zone Idu Aux Htr Relay Prars1 (1 Per IDU)
LG Electronics	Aux Heater Kit All Ducted/Cassette	PRARH0	Y	Y	N	LG Option 3: Aux Htr Relay Prarh0 Ducted, Cassette Idu (1 Per IDU)
LG Electronics	Third Party Tstst Method A Model Series IDU	PDRYCB300	Y	N	Optional	LG Option 4: Arnu Series IDU PDRYCB300+ 24 V Trans. + Thermostat (1Per IDU)
LG Electronics (Airzone)	Aidoo Pro	AZA16WSPLGE	N	Y	Y	The Airzone Aidoo Pro is compatible with all ducted and non-ducted units that have a CN_REMO plug. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the Aidoo Pro can be used on its own for the integrated control as it has a Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native LG controls, switchover can be done based off of outdoor temperature. LG Option 5: Arnu Series IDU + 2 Stage Tsat With Wired/Wireless/Internet Odt Sensing Wired Through Relay To Cn-Ext Of Any (1) IDU
LG Electronics	A Series Idu Model - Dry Contact Built In	ALL "A" SERIES IDU	Y	Y	Y	
LG MFG	Thermostat	PREMTVBCO	Y	Y	N	2 SET PT HTG&CLG 7DAY
LG MFG	Thermostat	PREMTBVC1	Y	Y	N	2 set pt htg&clg 7day/humid sensor opt-zigby occ sensors
LG MFG	Thermostat	PREMTCOOU	Y	Y	N	Simple Thermostat
LG MFG	Thermostat	PREMTA000	Y	Y	N	Premium LG Thermostat
LG MFG	Dry Contact	PDRYCB320	Y	N	N	Dry contact for third party t-stat
Mitsubishi Electric	Kumo Station	PAC-WHS01HC-E	N	N	Y	Requires an outdoor temperature sensor and each unit needs a Kumo Cloud interface
	Outdoor Temperature Sensor	C7089U1006/U				

	Kumo Cloud wireless interface	PAC-USWHS002-WF-1 or PAC-USWHS002-WF-2				
Mitsubishi Electric	Thermostat Interface	PAC-US444CN-1 or PAC-US445CN-1	Y	Y*	Y*	Requires a T-Stat Interface and transformer for each indoor unit, and a 2 stage thermostat by any manufacturer. ACTS AS IC WITH QPL LISTED THERMOSTAT. To operate the indoor unit via Thermostat Interface (PAC-US444CN-1) using a 24VAC thermostat in the heat pump configuration (using O/B with Y1 & Y2 output) requires a double pole-double throw relay, see Application Note 3044. *Depends on Thermostat Selected.
	Transformer	VP124-210				
Mitsubishi Electric	Kumo Cloud with IFTTT compatible Thermostat	PAC-USWHS002-WF-1 PAC-USWHS002-WF-2	N	Y	Y	IFTTT App connects Mitsubishi Electric Kumo Cloud with any IFTTT compatible thermostat. Current IFTTT compatible thermostats include Ecobee, and Honeywell as of 11/1/19. For list of devices, go to www.ifttt.com/services (Environment Control & Monitoring). Integration is capable by logging compatible thermostat and Kumo Cloud into IFTTT, then creating applet allowing IFTTT to adjust primary and secondary heating systems, based on outdoor temperature.
Mitsubishi Electric	CN24 Relay Kit and compatible indoor units	CN24RELAY-KIT-CM3	Y	N	N	Install CN24 relay kit in parallel with or without back-up heat thermostat to activate second stage on droop temperature. Outdoor balance point temperature can be set for CN24 activation on models with handheld control. Above high set temperature, only heat pump operation is available. When outdoor temperature is below balance point temperature setting, back-up heat is available when indoor temperature droops 2.7 F below set-point. Back up heat will operate until indoor temperature reaches set-point temperature of heat pump, heat pump continues to operate throughout. Compatible indoor units include Wall Mounted MSZ-ES Series, Floor Mounted MEZ-K1 Series, Ceiling Cassettes MSZ-SLZ.8, MSZ-M1Z, Ducted units.
Mitsubishi Electric	Airzone	AZZBSR2MEL	N	Y	Y	Compatible with Mitsubishi M-Series, P-Series, & S-Series indoor units. Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as well as differential temperature for activation of secondary sources. WiFi & Bacnet functionality optional.
Airzone (Mitsubishi)	Aidoo Pro	AZAI6WSPMEL	N	Y	Y	The Airzone Aidoo Pro is compatible with all ducted and non-ducted units that have a CN105 plug. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the Aidoo Pro can be used on its own for the integrated control as it has a Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native Mitsubishi controls, switchover can be done based off of outdoor https://doc.airzonecloud.com/Documentation/AZ6/AI6/FT_AZAI6WSPMEL_MUL.pdf
Airzone (Mitsubishi)	VAF	AZVAFCB2MEL	N	Y	Y	Compatible with Mitsubishi M-Series, P-Series, & S-Series indoor units. Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as well as differential temperature for activation of secondary sources. WiFi & Bacnet functionality optional.
Mitsubishi Electric	intelli-HEAT Cased Coil	PAA-A18AA1, PAA-A18BA1, PAA-A24AA1, PAA-A24BA1, PAA-A30AA1, PAA-A30BA, PAA-A36BA1, PAA-A36CA1, PAA-A42BA1, PAA-A42CA1	Y	N	N	Compatible with any thermostatically controlled ANSI Z21.47/CSA 2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11° F, 9° F, 14° F, 19° F, 27° F, 32° F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting
Resideo Technology Inc. under the Honeywell Home Brand	D6 Pro Wi-Fi Ductless Controller	DC6000WF1001/U	N	N	Y	This solution is cloud-based, and utilizes a D6 controller with the Mini-Split and a T Series Wi-Fi thermostat on the conventional HVAC system. This would be at a 1:1 relationship. There are no other devices needed other than the two thermostats. There is no additional wiring needed. A simple to use feature, curated and available in the Honeywell Home thermostat App, pairs the two devices in minutes and the cloud algorithm takes over from there. The D6 Controller will work with the Honeywell Home T5, T5+, T6, T9 and T10, demand response capable, smart thermostat line. These models include: RCHT8612WF2005/U or W; RCHT8610WF2006/U or W; RCHT9610WFSW2003/U or W; RCHT9510WFW2001/U or W; TH6220WF2006/U and TH6320WF2003/U. The D6 Controller and T-Series Thermostats can be found at the Resideo.com website for more information. (The D6 Controller is powered by 120V, it also uses a standard wall outlet).
Samsung HVAC	Thermostat Adaptor	MIM-A60UN	Y	N	N	Requires T-Stat adaptor (maximum 2 indoor units per adaptor), 24VAC transformer, and dual fuel thermostat by any connected.
Samsung HVAC	Samsung Wi-Fi Adapter	MIM-H04UN	N	Y	Y	Compatible with all Samsung: DVMs, single zone CAC systems, FJM systems with Ducted, Cassette, and/or Console units connected. Once the Wifi adaptor is installed the Smart Things App controls up to 16 indoor units simultaneously and the balance point chganger of the Honeywell thermostat. The following thermostats are required for the integration of secondary heat source. Honeywell: TH6320WF2003/U, TH6220WF2006/U, TH8321WF1001/U, TH9320WF5003/U. All Samsung residential wind free wall units already have Wifi adaptor pre-installed and would just require one of the listed thermostats.
Samsung HVAC	SmartThings with SmartThings compatible Thermostat	All Samsung SmartThings-enabled Mini-splits, Heat Pumps, Cassettes, etc. See Notes for Models.	N	Y	Y	Samsung HVAC products using SmartThings App to connect to any of the following ST enabled thermostats from the following brands: 2iig, American Standard, Ecobee, Fibaro, Nest, Honeywell, Lux, Nexia, Popo, Sinope, Stelpro, Trane, Zen. See link below https://www.smartthings.com/products-list *wifi enabled Dual Fuel Thermostat must be listed on IC QPL. Integration is possible by adding compatible thermostat to SmartThings App and automating controls through the App. The following Samsung HVAC models support SmartThings: WindFree 2.0, WindFree 2.0e, Max Heat 2.0, Max, Quantum 2.0, Free Joint Multi, Slim Duct, Free Join Multi Max Heat, WindFree Mini 4-way Cassette, Console, 360 Cassette, Windfree 4-way Cassette, Duct 5, Multi-Position Air Handler, High Wall, Light Commercial Outdoor Unit, Light Commercial Max Heat Outdoor Unit, Windfree 4-way Cassette Max Heat, Duct 5 Max Heat, Multi-Position Air Handler Max Heat, minus40 Low Ambient Cooling, DVM S Eco, DVM S Water, HSP Duct, OAP Duct, Big Ceiling, Under Ceiling, Glass Ceiling, 30, 36, 48, 60, 72, 84, 96, 108, 120, 144, 168, 180, 200, 225, 240, 270, 300, 324, 360, 396, 432, 468, 504, 540, 576, 612, 648, 684, 720, 756, 792, 828, 864, 900, 936, 972, 1008, 1044, 1080, 1116, 1152, 1188, 1224, 1260, 1296, 1332, 1368, 1404, 1440, 1476, 1512, 1548, 1584, 1620, 1656, 1692, 1728, 1764, 1800, 1836, 1872, 1908, 1944, 1980, 2016, 2052, 2088, 2124, 2160, 2196, 2232, 2268, 2304, 2340, 2376, 2412, 2448, 2484, 2520, 2556, 2592, 2628, 2664, 2700, 2736, 2772, 2808, 2844, 2880, 2916, 2952, 2988, 3024, 3060, 3096, 3132, 3168, 3204, 3240, 3276, 3312, 3348, 3384, 3420, 3456, 3492, 3528, 3564, 3600, 3636, 3672, 3708, 3744, 3780, 3816, 3852, 3888, 3924, 3960, 3996, 4032, 4068, 4104, 4140, 4176, 4212, 4248, 4284, 4320, 4356, 4392, 4428, 4464, 4500, 4536, 4572, 4608, 4644, 4680, 4716, 4752, 4788, 4824, 4860, 4896, 4932, 4968, 5004, 5040, 5076, 5112, 5148, 5184, 5220, 5256, 5292, 5328, 5364, 5400, 5436, 5472, 5508, 5544, 5580, 5616, 5652, 5688, 5724, 5760, 5796, 5832, 5868, 5904, 5940, 5976, 6012, 6048, 6084, 6120, 6156, 6192, 6228, 6264, 6300, 6336, 6372, 6408, 6444, 6480, 6516, 6552, 6588, 6624, 6660, 6696, 6732, 6768, 6804, 6840, 6876, 6912, 6948, 6984, 7020, 7056, 7092, 7128, 7164, 7200, 7236, 7272, 7308, 7344, 7380, 7416, 7452, 7488, 7524, 7560, 7596, 7632, 7668, 7704, 7740, 7776, 7812, 7848, 7884, 7920, 7956, 7992, 8028, 8064, 8100, 8136, 8172, 8208, 8244, 8280, 8316, 8352, 8388, 8424, 8460, 8496, 8532, 8568, 8604, 8640, 8676, 8712, 8748, 8784, 8820, 8856, 8892, 8928, 8964, 9000, 9036, 9072, 9108, 9144, 9180, 9216, 9252, 9288, 9324, 9360, 9396, 9432, 9468, 9504, 9540, 9576, 9612, 9648, 9684, 9720, 9756, 9792, 9828, 9864, 9900, 9936, 9972, 10008, 10044, 10080, 10116, 10152, 10188, 10224, 10260, 10296, 10332, 10368, 10404, 10440, 10476, 10512, 10548, 10584, 10620, 10656, 10692, 10728, 10764, 10800, 10836, 10872, 10908, 10944, 10980, 11016, 11052, 11088, 11124, 11160, 11196, 11232, 11268, 11304, 11340, 11376, 11412, 11448, 11484, 11520, 11556, 11592, 11628, 11664, 11700, 11736, 11772, 11808, 11844, 11880, 11916, 11952, 11988, 12024, 12060, 12096, 12132, 12168, 12204, 12240, 12276, 12312, 12348, 12384, 12420, 12456, 12492, 12528, 12564, 12600, 12636, 12672, 12708, 12744, 12780, 12816, 12852, 12888, 12924, 12960, 12996, 13032, 13068, 13104, 13140, 13176, 13212, 13248, 13284, 13320, 13356, 13392, 13428, 13464, 13500, 13536, 13572, 13608, 13644, 13680, 13716, 13752, 13788, 13824, 13860, 13896, 13932, 13968, 14004, 14040, 14076, 14112, 14148, 14184, 14220, 14256, 14292, 14328, 14364, 14400, 14436, 14472, 14508, 14544, 14580, 14616, 14652, 14688, 14724, 14760, 14796, 14832, 14868, 14904, 14940, 14976, 15012, 15048, 15084, 15120, 15156, 15192, 15228, 15264, 15300, 15336, 15372, 15408, 15444, 15480, 15516, 15552, 15588, 15624, 15660, 15696, 15732, 15768, 15804, 15840, 15876, 15912, 15948, 15984, 16020, 16056, 16092, 16128, 16164, 16200, 16236, 16272, 16308, 16344, 16380, 16416, 16452, 16488, 16524, 16560, 16596, 16632, 16668, 16704, 16740, 16776, 16812, 16848, 16884, 16920, 16956, 16992, 17028, 17064, 17100, 17136, 17172, 17208, 17244, 17280, 17316, 17352, 17388, 17424, 17460, 17496, 17532, 17568, 17604, 17640, 17676, 17712, 17748, 17784, 17820, 17856, 17892, 17928, 17964, 18000, 18036, 18072, 18108, 18144, 18180, 18216, 18252, 18288, 18324, 18360, 18396, 18432, 18468, 18504, 18540, 18576, 18612, 18648, 18684, 18720, 18756, 18792, 18828, 18864, 18900, 18936, 18972, 19008, 19044, 19080, 19116, 19152, 19188, 19224, 19260, 19296, 19332, 19368, 19404, 19440, 19476, 19512, 19548, 19584, 19620, 19656, 19692, 19728, 19764, 19800, 19836, 19872, 19908, 19944, 19980, 20016, 20052, 20088, 20124, 20160, 20196, 20232, 20268, 20304, 20340, 20376, 20412, 20448, 20484, 20520, 20556, 20592, 20628, 20664, 20700, 20736, 20772, 20808, 20844, 20880, 20916, 20952, 20988, 21024, 21060, 21096, 21132, 21168, 21204, 21240, 21276, 21312, 21348, 21384, 21420, 21456, 21492, 21528, 21564, 21600, 21636, 21672, 21708, 21744, 21780, 21816, 21852, 21888, 21924, 21960, 21996, 22032, 22068, 22104, 22140, 22176, 22212, 22248, 22284, 22320, 22356, 22392, 22428, 22464, 22500, 22536, 22572, 22608, 22644, 22680, 22716, 22752, 22788, 22824, 22860, 22896, 22932, 22968, 23004, 23040, 23076, 23112, 23148, 23184, 23220, 23256, 23292, 23328, 23364, 23400, 23436, 23472, 23508, 23544, 23580, 23616, 23652, 23688, 23724, 23760, 23796, 23832, 23868, 23904, 23940, 23976, 24012, 24048, 24084, 24120, 24156, 24192, 24228, 24264, 24300, 24336, 24372, 24408, 24444, 24480, 24516, 24552, 24588, 24624, 24660, 24696, 24732, 24768, 24804, 24840, 24876, 24912, 24948, 24984, 25020, 25056, 25092, 25128, 25164, 25200, 25236, 25272, 25308, 25344, 25380, 25416, 25452, 25488, 25524, 25560, 25596, 25632, 25668, 25704, 25740, 25776, 25812, 25848, 25884, 25920, 25956, 25992, 26028, 26064, 26100, 26136, 26172, 26208, 26244, 26280, 26316, 26352, 26388, 26424, 26460, 26496, 26532, 26568, 26604, 26640, 26676, 26712, 26748, 26784, 26820, 26856, 26892, 26928, 26964, 27000, 27036, 27072, 27108, 27144, 27180, 27216, 27252, 27288, 27324, 27360, 27396, 27432, 27468, 27504, 27540, 27576, 27612, 27648, 27684, 27720, 27756, 27792, 27828, 27864, 27900, 27936, 27972, 28008, 28044, 28080, 28116, 28152, 28188, 28224, 28260, 28296, 28332, 28368, 28404, 28440, 28476, 28512, 28548, 28584, 28620, 28656, 28692, 28728, 28764, 28800, 28836, 28872, 28908, 28944, 28980, 29016, 29052, 29088, 29124, 29160, 29196, 29232, 29268, 29304, 29340, 29376, 29412, 29448, 29484, 29520, 29556, 29592, 29628, 29664, 29700, 29736, 29772, 29808, 29844, 29880, 29916, 29952, 29988, 30024, 30060, 30096, 30132, 30168, 30204, 30240, 30276, 30312, 30348, 30384, 30420, 30456, 30492, 30528, 30564, 30600, 30636, 30672, 30708, 30744, 30780, 30816, 30852, 30888, 30924, 30960, 30996, 31032, 31068, 31104, 31140, 31176, 31212, 31248, 31284, 31320, 31356, 31392, 31428, 31464, 31500, 31536, 31572, 31608, 31644, 31680, 31716, 31752, 31788, 31824, 31860, 31896, 31932, 31968, 32004, 32040, 32076, 32112, 32148, 32184, 32220, 32256, 32292, 32328, 32364, 32400, 32436, 32472, 32508, 32544, 32580, 32616, 32652, 32688, 32724, 32760, 32796, 32832, 32868, 32904, 32940, 32976, 33012, 33048, 33084, 33120, 33156, 33192, 33228, 33264, 33300, 33336, 33372, 33408, 33444, 33480, 33516, 33552, 33588, 33624, 33660, 33696, 33732, 33768, 33804, 33840, 33876, 33912, 33948, 33984, 34020, 34056, 34092, 34128, 34164, 34200, 34236, 34272, 34308, 34344, 34380, 34416, 34452, 34488, 34524, 34560, 34596, 34632, 34668, 34704, 34740, 34776, 34812, 34848, 34884, 34920, 34956, 34992, 35028, 35064, 35100, 35136, 35172, 35208, 35244, 35280, 35316, 35352, 35388, 35424, 35460, 35496, 35532, 35568, 35604, 35640, 35676, 35712, 35748, 35784, 35820, 35856, 35892, 35928, 35964, 36000, 36036, 36072, 36108, 36144, 36180, 36216, 36252, 36288, 36324, 36360, 36396, 36432, 36468, 36504, 36540, 36576, 36612, 36648, 36684, 36720, 36756, 36792, 36828, 36864, 36900, 36936, 36972, 37008, 37044, 37080, 37116, 37152, 37188, 37224, 37260, 37296, 37332, 37368, 37404, 37440, 37476, 37512, 37548, 37584, 37620, 37656, 37692, 37728, 37764, 37800, 37836, 37872, 37908, 37944, 37980, 38016, 38052, 38088, 38124, 38160, 38196, 38232, 38268, 38304, 38340, 38376, 38412, 38448, 38484, 38520, 38556, 38592, 38628, 38664, 38700, 38736, 38772, 38808, 38844, 38880, 38916, 38952, 38988, 39024, 39060, 39096, 39132, 39168, 39204, 39240, 39276, 39312, 39348, 39384, 39420, 39456, 39492, 39528, 39564, 39600, 39636, 39672, 39708, 39744, 39780, 39816, 39852, 39888, 39924, 39960, 40000, 40040, 40080, 40120, 40160, 40200, 40240, 40280, 40320, 40360, 40400, 40440, 40480, 40520, 40560, 40600, 40640, 40680, 40720, 40760, 40800, 40840, 40880, 40920, 40960, 41000, 41040, 41080, 41120, 41160, 41200, 41240, 41280, 41320, 41360, 41400, 41440, 41480, 41520, 41560, 41600, 41640, 41680, 41720, 41760, 41800, 41840, 41880, 41920, 41960, 42000, 42040, 42080, 42120, 42160, 42200, 42240, 42280, 42320, 42360, 42400, 42440, 42480, 42520, 42560, 42600, 42640, 42680, 42720, 42760, 42800, 42840, 42880, 42920, 42960, 43000, 43040, 43080, 43120, 43160, 43200, 43240, 43280, 43320, 43360, 43400, 43440, 43480, 43520, 43560, 43600, 43640, 43680, 43720, 43760, 43800, 43840, 43880, 43920, 43960, 44000, 44040, 44080, 44120, 44160, 44200, 44240, 44280, 44320, 44360, 44400, 44440, 44480, 44520, 44560, 44600, 44640, 44680, 44720, 44760, 44800, 44840, 44880, 44920, 44960, 45000, 45040, 45080, 45120, 45160, 45200, 45240, 45280, 45320, 45360, 45400, 45440, 45480, 45520, 45560, 45600, 45640, 45680, 45720, 45760, 45800, 45840, 45880, 45920, 45960, 46000, 46040, 46080, 46120, 46160, 46200, 46240, 46280, 46320, 46360, 46400, 46440, 46480, 46520, 46560, 46600, 46640, 46680, 46720, 46760, 46800, 46840, 46880, 46920, 46960, 47000, 47040, 47080, 47120, 47160, 47200, 47240, 47280, 47320, 47360, 47400, 47440, 47480, 47520, 47560, 47600, 47640, 47680, 47720, 47760, 47800, 47840, 47880, 47920, 47960, 48000, 48040, 48080, 48120, 48160, 48200, 48240, 48280, 48320, 48360, 48400, 48440, 48480, 48520, 48560, 48600, 48640, 48680, 48720, 48760, 48800, 48840, 48880, 48920, 48960, 49000, 49040, 49080, 49120, 49160, 49200, 49240, 49280, 49320, 49360, 49400, 49440, 49480, 49520, 49560, 49600, 49640, 49680, 49720, 49760, 49800, 49840, 49880, 49920, 49960, 50000, 50040, 50080, 50120, 50160, 50200, 50240, 50280, 50320, 50360, 50400, 50440, 50480, 50520, 50560, 50600, 50640, 50680, 50720, 50760, 50800, 50840, 50880, 50920, 50960, 51000, 51040, 51080, 51120, 51160, 51200, 51240, 51280, 51320, 51360, 51400, 51440, 51480, 51520, 51560, 51600, 51640, 51680, 51720, 51760, 51800, 51840, 51880, 51920, 51960, 52000, 52040, 52080, 52120, 52160, 52200, 52240, 52280, 52320, 52360, 52400, 52440, 52480, 52520, 52560, 52600, 52640, 52680, 52720, 52760, 52800, 52840, 52880, 52920, 52960, 53000, 53040, 53080, 53120, 53160, 53200, 53240, 53280, 53320, 53360, 53400, 53440, 53480, 53520, 53560, 53600, 53640, 53680, 53720, 53760, 53800, 53840, 53880, 53920, 53960, 54000, 54040, 54080, 54120, 54160,

Pioneer	IFTTT	TST-APWIFIMUSB TST-LCACWIFIKP	N	Y	Y	IFTTT connects to the WiFi-enabled Pioneer split heat pump via the smartphone app, allowing for two-way communication between the mini split and the main heat source. Then an IFTTT applet can be created to allow for automatic changeover between the primary and secondary heat sources, based on the real-time outdoor temperature. The main heat source should be controlled via a WiFi and IFTTT compatible 3rd party thermostat, such as Nest, Ecobee, or Honeywell Home. For a full list...
Pioneer (Airzone)	Aidoo Pro	PAZA16WSP01	N	Y	Y	The Airzone Aidoo Pro is compatible with all Pioneer ducted and non-ducted units that have X-Y-E wiring. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can be done through the thermostat, or the Aidoo Pro can be used on its own for the integrated control as it has an Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic. If using the Aidoo Pro with native controls, switchover can be done based off of the current...
ZONEFIRST	Zone Control Panel	H32 & H32P	Y	N	N	Two and Three Zone Control for Single and Two Stage/Speed Heat Pumps w/Dual Fuel and most all conventional and wi-fi heat pump thermostats. Panel has multiple staging options: 1) from any zone thermostat, 2) adjustable timer on zone panel or 3) the percentage of zones calling. Less than 50%, first stage only, greater than 51% second stage. Dual fuel operation based on wired Outdoor Air Sensor (OAS) with adjustable temperature setting on zone panel.
ZONEFIRST	Zone Control Panel	MDP3	Y	N	N	Two and Three Zone Control Panel expandable to 100 Zones for Single and Two Stage/Speed Heat Pumps w/Dual Fuel and most all conventional and wi-fi heat pump thermostats. Panel has multiple staging options: 1) from any zone thermostat, 2) adjustable timer on zone panel, 3) the percentage of zones calling. Less than 50%, first stage only, greater than 51% second stage. Staging and Dual Fuel operation can also be based on wired Outdoor Air Sensor (OAS) with adjustable temperature setting on zone panel or the Leaving/Supply Air Sensor (ZPS) also with adjustable temp setting on panels menu driven display. Staging on supply air temp is a more advanced method for newer heat pumps with cold climate performance that can still deliver warm.
ZONEFIRST	BLISS Zone System	BZS	Y	Y	Y	Multi-Zone System with Intergrated Combination Light Switch Thermostats (LST) for each zone for remote Wi-Fi control and monitoring of system operation. Heat Pump staging and dual fuel changeover based on supply air sensors at each zone (WDS). Staging is set based on supply air temperatures rising and falling for both heating and cooling. When specific supply temp settings are not able to maintain the Bliss system stages and when needed will switch to dual fuel back-up for extreme temps. Remote monitoring and alerts can be sent when minimum system temps are not maintained.

Dual Fuel Thermostats (Qualify as Integrated Controls with eligible Heat Pump/Furnace combinations)						
Manufacturer	Model Name	Model #	24v (Y/N)	Communicating (Y/N)	WiFi Enabled (Y/N)	Notes
Amana Heating and Air Conditioning	Amana Smart Thermostat	ATST-CWE-BL-A	N	Y	Y	Compatible with all Amana Heating and Air conditioning brand communicating equipment
American Standard	Gold 824	ACONT824AS52D*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
American Standard	Silver 824	ACONT724AS42D*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
American Standard	Platinum 850	ACONT850AC52U*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
American Standard	Platinum 1050	AZON1050AC52Z*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
American Standard	Link 360	ALINK360A2VVU*	N	Y	Y	Product is a kit that includes 2 required pieces: a Smart Thermostat (AHUI2360A200U*) and System Controller (TSYS2C60A2VVU*). Remote wired outdoor temp sensor BAYSENS01ATEMPA.
AprilAire	8446, 8448	8446, 8448	Y			Non-Programmable
AprilAire	8465, 8466, 8476	8476	Y			Programmable 5/2 or 5/1/1
AprilAire	8600, 8620, 8910	8600, 8620, 8910	Y			Programmable 7-Day
AprilAire	Thermostat	S86NMMU	Y	N	N	Controls up to 4H/2C ducted heat pumps with dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable user-defined balance points for dual fuel switchover. Below the low balance point, only auxiliary heat is used. Above the high balance point, only compressor is used. In between, the thermostat will stage based on the demands of the room. All 4 stages have a programmable differential to customize staging thresholds. 24 VAC. Programmable schedule, but can be configured as non-programmable.
AprilAire	Thermostat	S86NMUPR	Y	N	N	Controls up to 4H/2C ducted heat pumps with dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable user-defined balance points for dual fuel switchover. Below the low balance point, only auxiliary heat is used. Above the high balance point, only compressor is used. In between, the thermostat will stage based on the demands of the room. All 4 stages have a programmable differential to customize staging thresholds. 24 VAC. Programmable schedule, but can be configured as non-programmable. Includes programmable IAQ relay for control of (1).
AprilAire	Wi-Fi Thermostat	S86WMUPR	Y	Y	Y	Controls up to 4H/2C ducted heat pumps with dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, 2100DT wireless outdoor sensor or home Wi-Fi network, the thermostat can enable user-defined balance points for dual fuel switchover. Below the low balance point, only auxiliary heat is used. Above the high balance point, only compressor is used. In between, the thermostat will stage based on the demands of the room. All 4 stages have a programmable differential to customize staging thresholds. 24 VAC. Programmable schedule, but can be configured as non-programmable. Includes programmable IAQ relay for control of (1) humidifier, dehumidifier or ventilator. Wi-Fi enabled for control of (1).
AprilAire	Thermostat	S84NSU	Y	N	N	Controls up to 2H/1C ducted heat pumps with dual fuel or 1H/1C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable user-defined balance points for dual fuel switchover. Below the low balance point, only auxiliary heat is used. Above the high balance point, only compressor is used. In between, the thermostat will stage based on the demands of the room. All stages have a programmable differential to customize staging thresholds. 24 VAC or 2 AA Batteries. Programmable schedule, but can be configured as non-programmable.
AprilAire	8476W, 8620W, 8910W, 8920W	8476W, 8620W, 8910W, 8920W	Y		Y	Programmable 7-Day
AprilAire	8800	8800	Y	Y		Programmable 7-Day
AprilAire	8810, 8820, 8830, 8840	8810, 8820, 8830, 8840	Y	Y	Y	Programmable 7-Day
Armstrong	Comfort Sync A3	507175-01	Y	Y	Y	Dual-fuel capable (Comfort Sync-enabled HP only) with two balance points.

Bosch	Bosch Connected Control BCC100 Thermostat	BCC100	Y	N	Y	Uses local weather for outdoor temperature and balance point
Bryant	Evolution System Control	SYSTXBEECC01	Y	Y	Y	
Bryant	COR	T6-WEM01-A	Y	N	Y	
Bryant	COR SC	TSTWHA01	Y	N	Y	
Bryant	COR 7C	TSTWRH01	Y	N	Y	
Building36	Alarm.com Smart Thermostat	ADC-T2000	Optional	Y	Y	Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled option. Dehumidifier and external baffle functionality
Building36	Alarm.com Smart Thermostat HD	ADC-T40K-HD	Y	Y	Y	24v operated touchscreen thermostat with up to 4 heat and 2 cool and dual fuel capability. Cellular enabled option. Dehumidifier, Humidifier, external baffle, and vent control functionality.
Building36	Alarm.com Smart Thermostat (Design Studio Series)	ADC-T3000	Optional	Y	Y	Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled option. Dehumidifier and external baffle functionality
Building36	Intelligent Thermostat	B36-T10	Optional	Y	N	Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled
Carrier	COR	TP-WEM01-A	Y	N	Y	Uses local weather for outdoor Temperature and Change over
Carrier	COR SC	TSTWHA01	Y	N	Y	Uses local weather for outdoor Temperature and Change over
Carrier	COR 7C	TSTWRH01	Y	N	Y	Uses local weather for outdoor Temperature and Change over
Carrier	Infinity System Control	SYSTXCCITC01-B, SYSTXCCWIC01-B	N	Y	Y	Available in black and white
Cielo WiGLE Inc.	Cielo Smart Thermostat	CT101WA	Y	N	Y	Universal 4 Heat/2 Cool/Variable Capacity. (1) Cielo Smart thermostat fetches external weather data through cloud to enable the interplay of appliances. (2) Cielo Smart Thermostats can also be used to connect to ductless appliances (mini split with IR control) linked through Cielo Linked (cloud platform). Cielo Linked enables the interplay of connected ductless systems and Compatible with all Daikin brand communicating equipment
Daikin	Daikin One Touch Smart Thermostat	DTST-TOU-A	N	Y	Y	Compatible with all Daikin brand communicating equipment
Daikin	One+	DTST-ONE-ADA-A	Y	Y	Y	Compatible with Daikin Mini-Split and Multi Split Heat Pump Products. Thermostat is provided with communication adaptor that requires 110-240 VAC power supply. Additional adaptor (KRP980B2E) required for connection to FTX__NMVJU indoor units. Refer to comprehensive guide at https://cms.daikincomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf
Daikin	One+	DTST-CWBSA-NI-A	Y	Y	Y	Compatible with qualifying Daikin Central Heat Pump Systems. Refer to comprehensive guide at https://cms.daikincomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf
Daikin (Airzone)	DKN Plus Interface	AZA16WSPDKC	N	Y	Y	Connects Daikin VRV, SkyAir or Mini-split indoor units to a secondary heat source via onboard relay output. Secondary heat source can be enable via outdoor temperature configure with a BLE application. Can also integrate a 3rd party thermostat with 2 stage heating to enable secondary heat source. Integrate ecobee and Honeywell thermostats with IFTTT for dual fuel control. Connects Daikin VRV, SkyAir or Mini-split indoor units to an alternative heat source via onboard relay output. Controller required for each indoor unit. Can be used with outdoor temperature sensor to enable secondary heat source.
Daikin	Adaptive Touch Controller	BACRC-T-P01	Y	Y	N	Connects Daikin VRV, SkyAir or Mini-split indoor units to an alternative heat source via onboard relay output. Controller required for each indoor unit. Can be used with outdoor temperature sensor to enable secondary heat source.
Daikin	Adaptive Touch Controller	BACRC-TH-P01	Y	Y	N	Connects Daikin VRV, SkyAir or Mini-split indoor units to an alternative heat source via onboard relay output. Controller required for each indoor unit. Can be used with outdoor temperature sensor to enable secondary heat source.
Daikin	Adaptive Touch Controller	BACRC-THO-P01	Y	Y	N	Connects Daikin VRV, SkyAir or Mini-split indoor units to an alternative heat source via onboard relay output. Controller required for each indoor unit. Can be used with outdoor temperature sensor to enable secondary heat source.
Daikin	Adaptive Touch Controller	BACRC-THOC-P01	Y	Y	N	Connects Daikin VRV, SkyAir or Mini-split indoor units to an alternative heat source via onboard relay output. Controller required for each indoor unit. Can be used with outdoor temperature sensor to enable secondary heat source.
Daikin	Wiring Adaptor PCB	KRP1C74/75	N	N	N	Connects Daikin VRV, SkyAir or Mini-split indoor units to a secondary heat source via onboard relay output. Install KRP1C74/75 with back up heat thermostat. Configure outdoor temperature lockout to enable secondary heat source https://daikinlibraryapi.daikincomfort.com/api/Download/GetDocument?id=f93267d4-303d-696b-9e5f-ff0000a9a572
Ecoer	Ecoer Smart Thermostat	EST1701	Y	Y	Y	The Ecoer Thermostat when coupled with the Ecoer Heat Pump will enable fuel switching at a predetermined outdoor temperature. The Ecoer Heat pump has an onboard outdoor ambient temperature sensor which can be programmed to initiate a second stage of heat at a predetermined outdoor temperature and during defrost operation. When coupled with the Ecoer EG910L Gateway, the switching temperature may be remotely programmed. Further, the Ecoer EST1701 has a two-speed indoor fan feature which allows the fan to a reduced speed when approaching the thermostat setpoint.
Ecoer	Ecoer Gateway	EG910L				The Ecoer Gaeway is a two way cellular enabled communication device which transmits operating data from the Ecoer heat pump to the Ecoer monitoring computer. When enabled, critical operating information is recorded and relayed back to the installing contractor via a web enabled App. temperature setpoints may be addressed remotely through the app to enable fuel
Ecobee	Ecobee 3 Lite	EB-STATE3LT***, EB-STATE3-01	Y	N	Y	Not a current model, but still available
Ecobee	Ecobee 4	EB-STATE4***	Y		Y	Ecobee 4 is now Ecobee Smart Thermostat, but Ecobee 4 is still available
Ecobee	Ecobee Smart Thermostat with Voice Control	EB-STATES***	Y	N	Y	Model numbers may be slightly different due to color or vendor
Ecobee	Ecobee Thermostat	EB-STATE6***	Y	N	Y	Model numbers may be slightly different due to color or vendor. External Temperature Detection, Time of Day Usage, Additional Home Temperature Sensor, Geofencing (User Device Based), Additional Occupancy Sensor, Occupancy Sensor on
Heil	Ion™ System Control	SYST0101CW	Y	Y	Y	
Honeywell Home	Prestige IAQ	YTHX9421R5085WW	Y		Y	Requires THM6000R7001 Internet Gateway
Honeywell Home	Prestige IAQ	YTHX9421R5101WW	Y		Y	Requires THM6000R7001 Internet Gateway
Honeywell Home	Smart Round	TH8732WFH 5002	Y	Y	Y	Use with C7089U Wired Outdoor Sensor
Honeywell Home	T6 Pro	TH6320U 2008	Y	N	N	Use with C7089U Wired Outdoor Sensor
Honeywell Home	T6 Pro Smart	TH6320WF 2003	Y	Y	Y	Two options: 1) Use with C7089U Wired Outdoor Sensor or 2) Use local weather thru WiFi for outdoor temp and changeover.
Honeywell Home	VisionPro 8000 Smart	TH8320R 1003	Y	Y	N/Y	Use with C7089R Wireless Outdoor Sensor. Needs HW Thm6000R 7001 Gateway For Wi-Fi
Honeywell Home	VisionPro 8000 Smart	TH8321R 1001	Y	Y	N/Y	Use with C7089R Wireless Outdoor Sensor. Needs HW Thm6000R 7001 Gateway For Wi-Fi
Honeywell Home	WiFi 9000	TH9320WF5003/U	Y	N	Y	Outdoor temperature and humidity via WiFi, appear after registration.
Honeywell Home	WiFi 8000	TH8321WF 1001	Y	N	Y	
Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel	HZ432	Y	N	N	Use with C7089U1006 outdoor sensor. Zone control for centrally ducted heat pump system.

Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel Kit	HZ432K	Y	N	N	Use with C7089U1006 outdoor sensor. Zone control for centrally ducted heat pump system.
Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel Kit	TZ-4	Y	N	N	Zone control for centrally ducted heat pump system. A C7089B1000 Outdoor Temperature Sensor and a C7735A1000 Discharge Air Temperature Sensor are required for dual fuel operation.
Honeywell Home/Resideo	T10 ProSmart with Redlink Sensor	THX321WFS2001W	Y	N	Y	Up to 3 Heat 2 Cool, 24v, with wireless indoor sensor, Can control Humidity or Ventillation
Honeywell Home/Resideo	T10 ProSmart	THX321WF2003W	Y	N	Y	Up to 3 Heat 2 Cool, 24v, with Humidity or Ventillation Control
Lennox Industries Inc.	S40 Smart Thermostat	22V24	Y	Y	Y	Universal 4 Heat/2 Cool/Variable Capacity
Lennox Industries Inc.	S30 Ultra Smart Thermostat	19V30	Y	Y	Y	Universal 4 Heat/2 Cool/Variable Capacity
Lennox Industries Inc.	E30 Smart Thermostat	15S63	Y	N	Y	Universal 4 Heat/2 Cool
Lennox Industries Inc.	M30 Smart Thermostat	15Z69	Y	N	Y	Universal 4 Heat/2 Cool
Lennox Industries Inc.	iComfort E30	E30	Y	N	Y	Universal Smart
Lennox Industries Inc.	iComfort M30	M30	Y	N	Y	Universal Smart
Lennox Industries Inc.	iComfort S30	S30	Y	Y	Y	Communicating Smart Thermostat
Lennox Industries Inc.	iComfort WiFi	WiFi	Y	Y	Y	Communicating Smart Thermostat
Lennox Industries Inc.	Harmony III	50S,023M5	Y	Y	N	Zoning system
LG Electronics	Thermostat	PREMTVB0C0	Y	Y	N	2 Set point Heating and Cooling 7-Day. Can act as Integrated Control for entire hot water zone if connected to largest indoor unit of Multihead MSHP system.
LG Electronics	Thermostat	PREMTBVC1	Y	Y	N	2 Set point Heating and Cooling 7-Day/Humid Sensor OPT-ZIGBY OCC Sensors. Can act as Integrated Control for entire hot water zone if connected to largest indoor unit of Multihead MSHP system.
LG Electronics	Thermostat	PREMTBVC2	N	Y	N	2 set pt htg&clg 7day/humid sensor opt-zigby occ sensors
LG Electronics	Thermostat	PREMTBVC3	N	Y	N	2 set pt htg&clg 7day/humid sensor opt-zigby occ sensors
LG Electronics	Thermostat	PREMTA000	Y	Y	N	Premium LG Thermostat
LG Electronics	Thermostat	PREMTBVC4	N	Y	N	2 set pt htg&clg 7day/humid sensor + zigby occ sensors
LG Electronics	Thermostat	PREMTC00U	N	Y	N	Simple Thermostat
LG Electronics	Thermostat	PREMTB100	N	Y	N	Standard III Wired remote
LG Electronics	Thermostat	PREMTA200	N	Y	Y	Deluxe LG Thermostat
LG Electronics	Dry Contact	PDRYCB320	N	N	N	Dry contact for third party t-stat
LG Electronics (Airzone)	Aidoo Pro	AZAI6WSPLGE	N	Y	Y	The Airzone Aidoo Pro is compatible with all ducted and non-ducted units that have a CN_REMO plug. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the Aidoo Pro can be used on its own for the integrated control as it has a Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native LG controls, switchover can be done based off of outdoor temperature with LG Electronics ducted indoor units using the CN_REMO plug. Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as well as differential temperature for activation of secondary sources. WIFI & Bacnet functionality optional.
LG Electronics (Airzone)	VAF	AZVAFCB2LGE	N	Y	Y	IFTTT App connects Mitsubishi Electric Kumo Cloud with any IFTTT compatible thermostat. Current IFTTT compatible thermostats include Ecobee, and Honeywell as of 11/1/19. For list of devices, go to www.ifttt.com/services (Environment Control & Monitoring). Integration is capable by logging compatible thermostat and Kumo Cloud into IFTTT, then creating applet allowing IFTTT to adjust primary and secondary heating systems, based on outdoor temperature.
Mitsubishi Electric	Kumo Cloud with IFTTT compatible Thermostat	PAC-USWHS002-WF-1 or PAC-USWHS002-WF-2	N	Y	Y	Nest Learning Thermostat Pro - 3rd Generation (Stainless Steel, Carbon Blk, White, Copper)
Google Nest	Nest Learning thermostat - Third Gen	T3007ES, T3008US, T3016US, T3017US, T3021US, GA02180-US	Y	N	Y	Works with 85% of systems (2H/1C or 1H/2C). Programmable 7-day thermostat with guided setup. Installed using our "Pro Flow" install experience made for professionals. Heat Pump Balance allows for auto switch over to conserve energy.
Google Nest	Nest Thermostat		Y	N	Y	
Google Nest	Nest Thermostat E	T4000ES	Y		Y	
Robertshaw	Robertshaw	9725I2	Y		Y	9725I2 Programmable Thermostat (3 Heat - 2 Cool)
Robertshaw	Robertshaw	9825I2	Y		Y	9825I2 Programmable Thermostat (3 Heat - 2 Cool)
Ruud	Econet Thermostat	ETST700SYS	Y	Y	Y	Amazon Alexa compatible for use with communicating Ruud equipment only.
Tekmar	Invita	564	Y	N	Y	2 wire stat with equipment interface
Tekmar	Invita	564B	Y	N	Y	same but black finish
Tekmar		557	Y	Y	Y	WiFi only with additional Gateway control
Tekmar		563	Y	N	Y	Stand alone with WiFi
Trane	XL 824	TCONT824AS52D*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
Trane	XR 724	TCONT724AS42D*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
Trane	XL 850	TCONT850ACS2U*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
Trane	XL 1050	TZON1050ACS2Z*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
Trane	Link 360	TLINK360A2VUU*	N	Y	Y	Product is a kit that includes 2 required pieces: a Smart Thermostat (THUI2360A200U*) and System Controller (TSYS2C60A2VUU*). Remote wired outdoor temp sensor BAYSENS01ATEMPA.