

Last update: 5/13/2024

Dual Fuel Thermostat:  
 Dual fuel thermostats must be capable of doing at least two stages of heat and two stages of cooling and able to automate the changeover between the primary and secondary heat source based on an outdoor temperature. The temperature sensing can be via Wi-Fi weather data or via a local hard wired temperature sensor then it would be approved for the KCPL.

Dual Fuel Thermostats (Qualify as Integrated Controls with eligible combinations)								Reference 1	Reference 2
Manufacturer	Model Name	Model #	24x (Y/N)	Communicating (Y/N)	WiFi Enabled (Y/N)	Notes			
Amana Heating and Air Conditioning	Amana Smart Thermostat	AT3T-CWE-BI-A	N	Y	Y	Compatible with all Amana Heating and Air conditioning brand communicating equipment			
American Standard	Gold 824	ACONT824AS520*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.			
American Standard	Silver 824	ACONT724AS420*	Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.			
American Standard	Platinum 850	ACONT850ACS2U*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).			
American Standard	Platinum 1050	AZON1050ACS2T*	Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).			
American Standard	Link 360	ALINK360AZVU*	N	Y	Y	Product is a kit that includes 2 required pieces: a Smart Thermostat (AHU12360AZ00U*) and System Controller (TY12C50AZVU*). Remote wired outdoor temp sensor BAYSENS01ATEMPA.			
Apriliaire	8446	8446	Y			Non-Programmable			
Apriliaire	8448	8448	Y			Non-Programmable			
Apriliaire	8476	8476	Y			Programmable 5/2 or 5/7/1			
Apriliaire	8600	8600	Y			Programmable 7-Day			
Apriliaire	8910	8910	Y			Programmable 7-Day			

AprIAire	Thermostat	S8MMU	Y	N	N	Controls up to 4H/2C ducted heat pumps with dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable user-defined balance points for dual fuel switchover. Below the low balance point, only auxiliary heat is used. Above the high balance point, only compressor is used. In between, the thermostat will stage based on the demands of the room. All 4 stages have a programmable differential to customize staging thresholds. 24 VAC. Programmable schedule, but can be configured as non-programmable.	
AprIAire	Thermostat	S8MMUR	Y	N	N	Controls up to 4H/2C ducted heat pumps with dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable user-defined balance points for dual fuel switchover. Below the low balance point, only auxiliary heat is used. Above the high balance point, only compressor is used. In between, the thermostat will stage based on the demands of the room. All 4 stages have a programmable differential to customize staging thresholds. 24 VAC. Programmable schedule, but can be configured as non-programmable. Includes programmable IAQ relay for control of (1) humidifier, dehumidifier or ventilator.	
AprIAire	Wi-Fi Thermostat	S8WHAUR	Y	Y	Y	Controls up to 4H/2C ducted heat pumps with dual fuel or 2H/2C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, ZIGBEE wireless outdoor sensor or home Wi-Fi network, the thermostat can enable user-defined balance points for dual fuel switchover. Below the low balance point, only auxiliary heat is used. Above the high balance point, only compressor is used. In between, the thermostat will stage based on the demands of the room. All 4 stages have a programmable differential to customize staging thresholds. 24 VAC. Programmable schedule, but can be configured as non-programmable. Includes programmable IAQ relay for control of (1) humidifier, dehumidifier or ventilator. Wi-Fi enabled for control via AprIAire Healthy Air app.	
AprIAire	Thermostat	S8NSU	Y	N	N	Controls up to 2H/1C ducted heat pumps with dual fuel or 1H/1C ducted conventional systems. When coupled with 8052 wired outdoor temperature sensor, the thermostat can enable user-defined balance points for dual fuel switchover. Below the low balance point, only auxiliary heat is used. Above the high balance point, only compressor is used. In between, the thermostat will stage based on the demands of the room. All stages have a programmable differential to customize staging thresholds. 24 VAC or 2 AA Batteries. Programmable schedule, but can be configured as non-programmable.	
AprIAire	8620W	8620W	Y		Y	Programmable 7-Day	
AprIAire	8910W	8910W	Y		Y	Programmable 7-Day	
AprIAire	8920W	8920W	Y		Y	Programmable 7-Day	
AprIAire		8800		8800	Y	Programmable 7-Day	
AprIAire		8840		8840	Y	Y	Programmable 7-Day
Armstrong	Comfort Sync A3	507175-01	Y	Y	Y	Dual-fuel capable (Comfort Sync-enabled HP only) with two balance points.	
Bosch	Bosch Connected Control BCC100 Thermostat	BCC100	Y	N	Y	Uses local weather for outdoor temperature and balance point	
Bryant	Evolution System Control	SYST8BECCD1-B	N	Y	Y	Available in black and white. Uses outdoor sensor for outdoor Temperature and Change over	
Bryant	Evolution System Control	SYST8BECCD1-C	N	Y	Y	Available in black and white. Uses outdoor sensor for outdoor Temperature and Change over	

Bryant	Evolution System Control	SYST8BECF01-B	N	Y	Y	Available in black and white. Uses outdoor sensor for outdoor Temperature and Change over
Bryant	Evolution System Control	SYST8BWE01-B	N	Y	Y	Available in black and white. Uses outdoor sensor for outdoor Temperature and Change over
Bryant	Evolution System Control	SYST8BWE01-C	N	Y	Y	Available in black and white. Uses outdoor sensor for outdoor Temperature and Change over
Bryant	Evolution System Control	SYST8BWEF01-B	N	Y	Y	Available in black and white. Uses outdoor sensor for outdoor Temperature and Change over
Bryant	Ecobee3.0 for Bryant Smart Thermostat with IntelSense	EB-STATELT8R-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Bryant	Ecobee3.0 for Bryant Smart Thermostat with IntelSense	EB-STATELT8R-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Bryant	Ecobee for Bryant Smart Thermostat Lite with IntelSense	EB-STATE78R-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Bryant	Ecobee for Bryant Smart Thermostat Premium with IntelSense	EB-STATE68R-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Bryant	Bryant Smart Thermostat	TSTAT8BEWF-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Bryant	Wi-Fi Programmable Controller	KSACN1501AAA		Yes	Yes	Wi-Fi & App Control. (Wired Programmable Controller + Crossover Coil interface kit) Only available for purchase with the model 45MULAQ. Dual Fuel Control
Bryant	Wi-Fi Programmable Controller	KSACN1701BAA	Yes	Yes	Yes	Two-Wire or 24V Wire Connection, Wi-Fi & App Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.
Bryant Building6	Wi-Fi Programmable Controller Alarm.com Smart Thermostat	KSACN1701AAA-ADC-T2000	Yes Optional	Yes Y	Yes Y	Two-Wire or 24V Wire Connection, Wi-Fi & App Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface. Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled option, Dehumidifier and external baffle functionality

Building36	Alarm.com Smart Thermostat HD	ADC-T4DK-HD	Y	Y	Y	24v operated touchscreen thermostat with up to 4 heat and 2 cool and dual fuel capability. Cellular enabled option. Dehumidifier, Humidifier, external baffle, and vent control functionality.
Building36	Alarm.com Smart Thermostat (Design Studio Series)	ADC-T300	Optional	Y	Y	Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled option. Dehumidifier and external baffle functionality
Building36	Intelligent Thermostat	836-T10	Optional	Y	N	Up to 4 heat 2 cool, 24v or battery operated. Cellular enabled
Carrier	Infinity System Control	SYSTXCOTD1-B	N	Y	Y	Available in black and white
Carrier	Infinity System Control	SYSTXCWICD1-B	N	Y	Y	Available in black and white
Carrier	Wi-Fi Programmable Controller	KSACN1501AAA	Yes	Yes	Yes	Wi-Fi & App Control. (Wired Programmable Controller + Crossover Coil Interface Kit) Only available for purchase with the model 45MULAQ. Dual Fuel Control
Carrier	Wi-Fi Programmable Controller	KSACN1701BAA	Yes	Yes	Yes	Two-Wire or 24V Wire Connection, Wi-Fi & App Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.
Carrier Cielo WGIc Inc.	Wi-Fi Programmable Controller Cielo Smart Thermostat	KSACN1701AAA CT101WA	Yes Y	Yes N	Yes Y	Two-Wire or 24V Wire Connection, Wi-Fi & App Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface. Universal 4 Heat/2 Cool/Variable Capacity (1) Cielo Smart thermostat fetches external weather data through cloud to enable the interplay of appliances. (2) Cielo Smart Thermostat can also be used to connect to ductless appliances (mini split with IR control) linked through Cielo Linked (cloud platform). Cielo Linked enables the interplay of connected ductless systems and conventional ducted HVAC system. <a href="https://cms.dalnicomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf">https://cms.dalnicomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf</a>
Copeland	Sens Touch 2 smart thermostat - White	1F96U-42WF				Energy Star rated. Multi-Stage Universal touchscreen thermostat. Dual fuel capable. Compatible with indoor remote wireless sensors (sold separately). Max of fifteen sensors per Sens Touch 2 thermostats.
Daikin	Daikin One Touch Smart Thermostat	DTST-TDU-A	N	Y	Y	Compatible with all Daikin brand communicating equipment <a href="https://cms.dalnicomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf">https://cms.dalnicomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf</a>
Daikin	One+	DTST-ONE-ADA-A	Y	Y	Y	Compatible with Daikin Mini-Split and Multi-Split Heat Pump Products. Thermostat is provided with communication adaptor that requires 110-240 VAC power supply. Additional adaptor (9898820) required for connection to CTX_MINISPLIT indoor units refer to comprehensive guide at: <a href="https://cms.dalnicomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf">https://cms.dalnicomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf</a>
Daikin	One+	DTST-CWBSA-NI-A	Y	Y	Y	Compatible with qualifying Daikin Central Heat Pump Systems. Refer to comprehensive guide at: <a href="https://cms.dalnicomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf">https://cms.dalnicomfort.com/docs/default-source/default-document-library/manual/pm-one-st.pdf</a>

Daikin	One+	DTST-CWBSA-NI-B	Y	Y	Y	Compatible with all Daikin, Arnia, and Goodman brand communicating equipment.
Daikin	Wiring Adaptor PCB	KRP1C74/75	N	N	N	Connects Daikin VRV, SkyAir or Mini-split indoor units to a secondary heat source via onboard relay output. Install KRP1C74/75 with back up heat thermostat. Configure outdoor temperature lookout to enable secondary heat source: <a href="https://daikinbraryapi.daikincomfort.com/api/Download?refDocumentId=49326746-303d-696b-9d5f-f0000a6b572">https://daikinbraryapi.daikincomfort.com/api/Download?refDocumentId=49326746-303d-696b-9d5f-f0000a6b572</a>
Daikin (Arizona)	DKN Plus Interface	AZ46HSPDC	N	Y	Y	Connects Daikin VRV, SkyAir or Mini-split indoor units to a secondary heat source via onboard relay output. Secondary heat source can be enable via outdoor temperature configure with BLE application. Can also integrate a 3rd party thermostat with 2 stage heating to enable secondary heat source. Integrate ecobee and Honeywell thermostats with PTFT for dual fuel control
Ecobee	Ecobee Thermostat	EB-STATE6***	Y	N	Y	Model numbers may be slightly different due to color or vendor. External Temperature Detection, Time of Day Usage, Additional Home Temperature Sensor, Geofencing (User Device Based), Additional Occupancy Sensor, Occupancy Sensor on Device, Humidity Sensing
Ecobee	Ecobee Thermostat	EB-STATE7P-01	Y	N	Y	
Ecoer	Ecoer Smart Thermostat	EST02			Y	
Ecoer	Ecoer Smart Thermostat	EST1701	Y	Y	Y	The Ecoer Thermostat when coupled with the Ecoer Heat Pump will enable fuel switching at a predetermined outdoor temperature. The Ecoer Heat pump has an onboard outdoor ambient temperature sensor which can be programmed to initiate a second stage of heat at a predetermined outdoor temperature and during defrost operation. When coupled with the Ecoer EOP10L Gateway, the switching temperature may be remotely programmed. Further, the Ecoer EST1701 has a two-speed indoor fan feature which allows the fan to a reduced speed when approaching the thermostat setpoint.
Ecoer	Ecoer Gateway	EOP10L				The Ecoer Gateway is a two way cellular enabled communication device which transmits operating data from the Ecoer heat pump to the Ecoer monitoring computer. When enabled, critical operating information is recorded and relayed back to the installing contractor via a web enabled App. Temperature setpoints may be addressed remotely through the app to enable fuel switching setpoints.
Goodman	Goodman GTST Connected Thermostat	GTST-CW-WHA	N	Y	Y	Compatible with all Daikin, Arnia, and Goodman brand communicating equipment.
Google	Next Learning Thermostat (4th gen)	GA05169-US	Y	Y	Y	The Next Learning Thermostat (4th gen) works with most 24V systems, including gas, electric, oil, forced air, heat pump, and radiant. It can control Heating 1, 2, and 3 stages (W1, W2, W3); Cooling 1 and 2 stages (Y1, Y2); Heat pump with auxiliary and emergency heat (O/B, AUX, E); Fan (S, G2, G3); Power (C, RH, RC); Humidifier and dehumidifier (HUM, DEHUM); Ventilation (VENT). The Next Learning Thermostat 1" connector can accept one of these wires: W3, E, HUM, or DEHUM. The AQ1 and AQ2 connectors can accept 1-wire or 2-wire VENT, HUM, or DEHUM.
Google	Next Learning Thermostat (4th gen)	GA05551-US	Y	Y	Y	The Next Learning Thermostat (4th gen) works with most 24V systems, including gas, electric, oil, forced air, heat pump, and radiant. It can control Heating 1, 2, and 3 stages (W1, W2, W3); Cooling 1 and 2 stages (Y1, Y2); Heat pump with auxiliary and emergency heat (O/B, AUX, E); Fan (S, G2, G3); Power (C, RH, RC); Humidifier and dehumidifier (HUM, DEHUM); Ventilation (VENT). The Next Learning Thermostat 1" connector can accept one of these wires: W3, E, HUM, or DEHUM. The AQ1 and AQ2 connectors can accept 1-wire or 2-wire VENT, HUM, or DEHUM.
Google	Next Learning Thermostat (4th gen)	GA05171-US	Y	Y	Y	The Next Learning Thermostat (4th gen) works with most 24V systems, including gas, electric, oil, forced air, heat pump, and radiant. It can control Heating 1, 2, and 3 stages (W1, W2, W3); Cooling 1 and 2 stages (Y1, Y2); Heat pump with auxiliary and emergency heat (O/B, AUX, E); Fan (S, G2, G3); Power (C, RH, RC); Humidifier and dehumidifier (HUM, DEHUM); Ventilation (VENT). The Next Learning Thermostat 1" connector can accept one of these wires: W3, E, HUM, or DEHUM. The AQ1 and AQ2 connectors can accept 1-wire or 2-wire VENT, HUM, or DEHUM.
Google	Next Learning Thermostat (4th gen)	GA05560-US	Y	Y	Y	The Next Learning Thermostat (4th gen) works with most 24V systems, including gas, electric, oil, forced air, heat pump, and radiant. It can control Heating 1, 2, and 3 stages (W1, W2, W3); Cooling 1 and 2 stages (Y1, Y2); Heat pump with auxiliary and emergency heat (O/B, AUX, E); Fan (S, G2, G3); Power (C, RH, RC); Humidifier and dehumidifier (HUM, DEHUM); Ventilation (VENT). The Next Learning Thermostat 1" connector can accept one of these wires: W3, E, HUM, or DEHUM. The AQ1 and AQ2 connectors can accept 1-wire or 2-wire VENT, HUM, or DEHUM.

Google Nest	Nest Learning Thermostat 3rd Gen	T3018US	Y	N	Y	
Google Nest	Nest Learning Thermostat 3rd Gen	T3019US	Y	N	Y	
Google Nest	Nest Learning Thermostat 3rd Gen	T3012US	Y	N	Y	
Google Nest	Nest Learning Thermostat - Third Gen	T3007ES	Y	N	Y	Nest Learning Thermostat Pro - 3rd Generation (Stainless Steel, Carbon Blk, White, Copper)
Google Nest	Nest Learning Thermostat - Third Gen	T3008US	Y	N	Y	Nest Learning Thermostat Pro - 3rd Generation (Stainless Steel, Carbon Blk, White, Copper)
Google Nest	Nest Learning Thermostat - Third Gen	T3016US	Y	N	Y	Nest Learning Thermostat Pro - 3rd Generation (Stainless Steel, Carbon Blk, White, Copper)
Google Nest	Nest Learning thermostat - Third Gen	T3017US	Y	N	Y	Nest Learning Thermostat Pro - 3rd Generation (Stainless Steel, Carbon Blk, White, Copper)
Google Nest	Nest Learning Thermostat - Third Gen	T3021US	Y	N	Y	Nest Learning Thermostat Pro - 3rd Generation (Stainless Steel, Carbon Blk, White, Copper)
Google Nest	Nest Thermostat	GA02180-US	Y	N	Y	Works with 85% of systems (2H/1C or 1H/2C). Programmable 7-day thermostat with guided setup. Installed using our "Pro Flow" install experience made for professionals. Heat Pump Balance allows for auto switch over to conserve energy.
Google Nest	Nest Thermostat E	T4000ES	Y		Y	
Google Nest	Nest Thermostat	GA01334-US	Y	Y	Y	The Nest Thermostat works with most 24V heating and cooling systems, including furnaces, air conditioners, boilers, and heat pumps with either forced air or radiant delivery. It works with conventional systems that have one stage of heating and cooling and a second stage of either heating or cooling. It works with heat pumps that have one stage of heating and cooling and either aux or emergency heat. And it works with HVAC fans.
Google Nest	Nest Thermostat	GA02081-US	Y	Y	Y	The Nest Thermostat works with most 24V heating and cooling systems, including furnaces, air conditioners, boilers, and heat pumps with either forced air or radiant delivery. It works with conventional systems that have one stage of heating and cooling and a second stage of either heating or cooling. It works with heat pumps that have one stage of heating and cooling and either aux or emergency heat. And it works with HVAC fans.
Google Nest	Nest Thermostat	GA02082-US	Y	Y	Y	The Nest Thermostat works with most 24V heating and cooling systems, including furnaces, air conditioners, boilers, and heat pumps with either forced air or radiant delivery. It works with conventional systems that have one stage of heating and cooling and a second stage of either heating or cooling. It works with heat pumps that have one stage of heating and cooling and either aux or emergency heat. And it works with HVAC fans.

Google Nest	Nest Thermostat	GA02083-US	Y	Y	Y	The Nest Thermostat works with most 24V heating and cooling systems, including furnaces, air conditioners, boilers, and heat pumps with either forced air or radiant delivery. It works with conventional systems that have one stage of heating and cooling and a second stage of either heating or cooling. It works with heat pumps that have one stage of heating and cooling and either aux or emergency heat. And it works with HVAC fans.
Hell	Ion™ System Control	SYST0101CW	Y	Y	Y	
Honeywell	FocusPRO S200 Smart Thermostat	TH3120WF4010				Wi-Fi dual fuel Thermostat, Energy Star Certified
Honeywell	FocusPRO P200 Programmable Thermostat	TH2120U4006				Non-connected dual fuel programmable/non-programmable thermostat
Honeywell	FocusPRO N200 Non-Programmable Thermostat	TH1120U4002				Non-connected dual fuel thermostat
Honeywell Home	Prestige IAQ	YH9342185085WW	Y		Y	Requires THM60087001 Internet Gateway
Honeywell Home	Prestige IAQ	YH9342185101WW	Y		Y	Requires THM60087001 Internet Gateway
Honeywell Home	T6 Pro	TH3120U 2008	Y	N	N	Use with C7088U Wired Outdoor Sensor
Honeywell Home	T6 Pro Smart	TH3120WF 2003	Y	Y	Y	Two options: 1) Use with C7088U Wired Outdoor Sensor or 2) Use local weather thru WiFi for outdoor temp and changover.
Honeywell Home	VisioPro 8000 Smart	TH3120R 1003	Y	Y	N/Y	Use with C7088R Wireless Outdoor Sensor. Needs HW THM6008 7001 Gateway For Wi-Fi
Honeywell Home	VisioPro 8000 Smart	TH3121R 1001	Y	Y	N/Y	Use with C7088R Wireless Outdoor Sensor. Needs HW THM6008 7001 Gateway For Wi-Fi
Honeywell Home	WiFi 9000	TH9120WF5003/U	Y	N	Y	Outdoor temperature and humidity via WiFi, appear after registration.
Honeywell Home	WiFi 8000	TH3121WF 1001	Y	N	Y	

Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel	H2432	Y	N	N	Use with C708BU1006 outdoor sensor. Zone control for centrally ducted heat pump system.
Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel Kit	H2432K	Y	N	N	Use with C708BU1006 outdoor sensor. Zone control for centrally ducted heat pump system.
Honeywell Home/Resideo	True Zone Dual Fuel Zoning Panel Kit	TZ-4	Y	N	N	Zone control for centrally ducted heat pump system. A C709981000 Outdoor Temperature Sensor and a C7735A1000 Discharge Air Temperature Sensor are required for dual fuel operation
Honeywell Home/Resideo	T10 ProSmart	THX121WF2003W	Y	N	Y	Up to 3 Heat 2 Cool, 24v, with Humidity or Ventilation Control
Honeywell Home/Resideo	T10+ Pro Smart Thermostat with RedLINK™ 3.0 includes room sensor	THX121WF13001W	Y	N	Y	
Honeywell Home/Resideo	Elite Pro	THX120086/U	Y	Y	Y	
Honeywell Home/Resideo	Elite Pro	THX1200W5/U	Y	Y	Y	
Honeywell Home/Resideo	Elite Pro	YTHX120086/U	Y	Y	Y	kit w/sensor
Honeywell Home/Resideo	Elite Pro	YTHX1200W5/U	Y	Y	Y	kit w/sensor
Honeywell Home/Resideo	Elite Pro	YTHX120088/U	Y	Y	Y	kit with EIM
Honeywell Home/Resideo	Elite Pro	YTHX1200W7/U	Y	Y	Y	kit with EIM
Honeywell Home/Resideo	Elite Pro	THX110084/U	Y	Y	Y	
Honeywell Home/Resideo	Elite Pro	THX1100W3/U	Y	Y	Y	

Honeywell Home/Resideo	Elite Pro	THX1008Z/U	Y	Y	Y	
Honeywell Home/Resideo	Elite Pro	THX100W1/U	Y	Y	Y	
Honeywell Home/Resideo	Elite Pro	THX008Z/U	Y	Y	Y	
Honeywell Home/Resideo	Elite Pro	THX00W1/U	Y	Y	Y	
ICP	Wi-Fi Programmable Controller	KSACN1501AAA	Yes	Yes		Wi-Fi & App Control. (Wired Programmable Controller + Crossover Coil Interface Kit) Only available for purchase with the model 45MULAQ. Dual Fuel Control
ICP	24V Interface Gen 3	KSACD505123D	Yes	Yes		Wi-Fi & App Control. (Wired Programmable Controller + Crossover Coil Interface Kit) Only available for purchase with the model 45MULAQ. Dual Fuel Control
ICP	Wi-Fi Programmable Controller	KSACN1701BAA	Yes	Yes	Yes	Two-Wire or 24V Wire Connection, Wi-Fi & App-Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.
ICP Innovair Solutions USA	Wi-Fi Programmable Controller	KSACN1701AAA 171317100009536	Yes N	Yes Y	Yes Y	Two-Wire or 24V Wire Connection, Wi-Fi & App-Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.
Ion	Ion Gray Smart Thermostat	TSTATIEWF-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Lennox Industries Inc.	Harmony III	X9953	Y	Y	N	Zoning system; updated model number.
Lennox Industries Inc.	L40 Smart Programmable Thermostat	L40	Y	Y	Y	
Lennox Industries Inc.	S40 Smart Thermostat	22V24	Y	Y	Y	Universal 4 Heat/2 Cool/Variable Capacity

Lennox Industries Inc.	E30 Smart Thermostat	15563	Y	N	Y	Universal 4 Heat/2 Cool
Lennox Industries Inc.	M30 Smart Thermostat	15269	Y	N	Y	Universal 4 Heat/2 Cool
Lennox Industries Inc.	Comfort E30	E30	Y	N	Y	Universal Smart
Lennox Industries Inc.	Comfort M30	M30	Y	N	Y	Universal Smart
Lennox Industries Inc.	Harmony III	505.023M5	Y	Y	N	Zoning system
LG Electronics	Thermostat	PREMTBVC2	N	Y	N	2 set pt.htg&clg 7day/humid sensor opt.igby occ sensors
LG Electronics	Thermostat	PREMTBVC3	N	Y	N	2 set pt.htg&clg 7day/humid sensor opt.igby occ sensors
LG Electronics	Thermostat	PREMTBVC4	N	Y	N	2 set pt.htg&clg 7day/humid sensor + igby occ sensors
LG Electronics	Thermostat	PREMTD00U	N	Y	N	Simple Thermostat
LG Electronics	Dry Contact	PORVCB320	N	N	N	Dry contact for third party t-stat
LG Electronics	ZINU Series 16s Model - Dry Contact Built In	ALL "ZINU" SERIES 16U	Y	Y	Y	ZINU Series 16U + 2 Stage Tstat With Wired/Wireless/Internet Oct Sensing Wired Through Relay To CH_CC Of Any (L) 16U
LG Electronics (Airzone)	VAF	AZVAFCB2LGE	N	Y	Y	Compatible with LG Electronics ducted indoor units using the CH_REMOTE plug - Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as well as differential temperature for activation of secondary sources. WiFi & BACnet functionality optional.
LG MFG	Thermostat	PREMTA201	Y	Y	Y	WiFi connection built in, requires a ThinkQ account

LG MFG	Cloud Gateway	PWFM08300	Y	Y	Y	Connects ODU to wi-fi and allows IDUs on the system to be controlled via ThinkQ. Requires ThinkQ Account.	
Mitsubishi Electric	Kumo Cloud	PAC-USWH5002-WF-1	N	Y	Y	PAC-USWH5002-WF-1 has been discontinued by Mitsubishi. Projects installed using this adapter to satisfy the Integrated Controls (IC) requirement on or before December 31, 2025 will remain eligible for incentives, but projects installed using this adapter on or after January 1, 2026 will no longer be eligible for incentives. PAC-USWH5002-WF-2 is the latest adapter model and will remain on the OPI.	
Mitsubishi Electric	Kumo Cloud	PAC-USWH5003-WF-2	N	Y	Y		
MIRCOOL, LLC	MIRCOOL Smart Thermostat	MST04	Y	N	Y	The MIRCOOL Smart Thermostat is compatible with conventional HVAC systems, supporting up to 2 stages of heating and 2 stages of cooling. For heat pump systems, it accommodates up to 4 stages of heating and 2 stages of cooling. The MIRCOOL Smart Thermostat also stores projected temperature data for the next 72 hours, ensuring continuous operation and decision making even if the Wi-Fi connection is temporarily lost.	
Payne	Wi-Fi Programmable Controller	KSACN1501AAA		Yes	Yes	Wi-Fi & App Control. (Wired Programmable Controller + Crossover Coil Interface Kit) Only available for purchase with the model 45MULAQ. Dual Fuel Control	
Payne	Wi-Fi Programmable Controller	KSACN1701BAA	Yes	Yes	Yes	Two-Wire or 24V Wire Connection, Wi-Fi & App-Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.	
Payne Robertshaw	Wi-Fi Programmable Controller Robertshaw	KSACN1701AAA 972512	Yes Y	Yes Y	Yes Y	Two-Wire or 24V Wire Connection, Wi-Fi & App-Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface. 972512 Programmable Thermostat (3 Heat - 2 Cool)	
Robertshaw	Robertshaw	982512	Y		Y	982512 Programmable Thermostat (3 Heat - 2 Cool)	
Ruud	Econet Thermostat	ETST7005YS	Y	Y	Y	Amazon Alexa compatible for use with communicating Ruud equipment only.	
Takmar	Invia		564	Y	N	Y	2 wire stat with equipment interface
Takmar	Invia	564B	Y	N	Y	same but black finish	
Takmar			557	Y	Y	Y	Wifi only with additional Gateway control

Tekmar			5E3	Y	N	Y	Stand alone with WiFi
Trane	Piact Thermostat	BAYSTAT148		Y	Y	Y	<a href="https://library.transtechnologies.com/public/commercial-hvac/kitparts/installation%20operation%20and%20Maintenance/BAS-VW0786-EN_11082023.pdf">https://library.transtechnologies.com/public/commercial-hvac/kitparts/installation%20operation%20and%20Maintenance/BAS-VW0786-EN_11082023.pdf</a>
Trane	XL 824	TCONT8244532D*		Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
Trane	X8724	TCONT7244542D*		Y	N	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible.
Trane	XL 850	TCONT8504532U*		Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
Trane	XL 1050	TZON10504532*		Y	Y	Y	Remote wired outdoor temp sensor BAYSENS01ATEMPA. Boiler systems compatible (requires BAYWAKIT24VACA accessory).
Trane	Link 360	TLINK360A2VVU*		N	Y	Y	Product is a kit that includes 2 required pieces: a Smart Thermostat (THU2360A2D0U*) and System Controller (TS162C60A2VVU*). Remote wired outdoor temp sensor BAYSENS01ATEMPA.
Venstar	ColorTouch	T7900		Yes	No	Yes	
Venstar	ColorTouch	T7850		Yes	No	Yes	
Venstar	Explorer IAQ	T8950-IAQ		Yes	No	Yes	

Last update: 5/13/2024

**Integrated Controls Package**  
 Integrated control solutions are provided by the heat pump manufacturers for listing on the ICPL. This is meant to ensure solutions are approved by the manufacturer and do not invalidate the manufacturer warranty for equipment installed. To qualify, the IC must switch from heat pumps as the primary to the combustion system as the secondary. The changeover must be done automatically based on a preset outdoor temperature. The outdoor temperature can be determined by a local outdoor temperature sensor or via Wi-Fi weather data. For example, all lockouts through heat pumps in green heating zone must switch to electric boiler via IC communication with no user interaction.

Integrated Controls Package										Reference 1	Reference 2
Manufacturer	Model Name	Model #	24-1(Y/N)	Communicating (Y/N)	WiFi Enabled (Y/N)	Notes					
Aeon	VCDX	VCDX	Y	Y	N						
Aeon	VCDX	VCDX-2	Y	Y	N						
Aeon	VCDX	VCDX-IP	Y	Y	N						
Aeon	VCDX	VCDX2	Y	Y	N						
Aeon	VCDX	VCDX-454	Y	Y	N						
Arizona (Fujitsu)	Arizona Aidoo Pro (2 wire/UART)	AZAWSPFU2	N	Y	Y	Aidoo Pro Modules communicate with the Fujitsu system through UART connection for 2 wire units and to the control terminals for 3 wire units. The controls allow for optional simultaneous use of Fujitsu control and/or 3rd party thermostat from QPL. Dual full thermostat replaces existing heat thermostat. Aidoo Pro module has "AUX" heat output, can be used stand alone without additional controls to disable heat pump operation and close AUX output through "ARIZONE CLOUD" app programming. FT_AZAWSPFU2_MUL.pdf (arizonecloud.com)					
Arizona (Mitsubishi)	Aidoo Pro	AZAWSPMEL	N	Y	Y	The Arizona Aidoo Pro is compatible with all ducted and non-ducted units that have a CN105 plug. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can be done through the thermostat on the Aidoo Pro or can be used on its own for the integrated control as it has a aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native Mitsubishi control, switchover can be done based off of outdoor temperature through the app. https://doc.arizonecloud.com/Documentation/AZU/A6/FT_AZAWSPMEL_MUL.pdf					
Arizona (Mitsubishi)	VAF	AZVAFB2MEL	N	Y	Y	Compatible with Mitsubishi M Series, P Series, & S Series indoor units. Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as well as differential temperature for activation of secondary sources. WiFi & BACnet functionality optional.					
Arizona North America Corp	Aidoo Pro ST1	AZAWSP2***	Y	Y	Y	Cloud based remote management & integration; dual Wi-Fi; supports Modbus/BACnet and API integrations.					
Arizona North America Corp	Aidoo Pro HUB	AZABHB2***	N	Y	Y	Cloud device with Ethernet or Wi-Fi; supports Modbus/BACnet and API integrations; auxiliary heat control/locking.					
Arizona North America Corp	Aidoo Pro Wi-Fi	AZAWSP***	N	Y	Y	Cloud + dual Wi-Fi; auxiliary heat control/locking; supports Modbus/BACnet and API integrations.					
Amana Heating and Air Conditioning	Amana Smart Thermostat	ATST-CWE-8L-A	N	Y	Y	Compatible with all Amana Heating and Air conditioning brand communicating equipment					

Apriliaire	Zone Panel	6403	Y	N	N	One zone panel is needed for up to three zones. Works with most brand thermostats to control conventional heat/cool or heat pump systems with electric or fossil fuel backup heating systems. The zone panel can control single or multi-stage equipment and works with normally open/power close, normally closed/power open, or power open/power close dampers. Wired outdoor temperature sensor can be used to automatically lock out compressor on low temperature or backup heat on high outdoor temperature. Integrated LEDs indicate equipment function.
Apriliaire	Zone Panel	6404	Y	N	N	One zone panel is needed for up to four zones, expandable up to twelve zones with additional #6403 panels. Works with most brand thermostats to control conventional heat/cool or heat pump systems with electric or fossil fuel backup heating systems. The zone panel can control single or multi-stage equipment and works with normally open/power close, normally closed/power open, or power open/power close dampers. Wired outdoor temperature sensor can be used to automatically lock out compressor on low temperature or backup heat on high outdoor temperature. Integrated LEDs indicate equipment function.
Azeel Zoning Technology	HeatPump Pro	PAN-HP902	Y	N	N	The HeatPump Pro is a Forced Air HVAC Zoning Control Compatible with conventional Heat Pump and Dual Fuel Systems. The HeatPump Pro IC automatically switches from using heat pumps as the primary source of heat, to a secondary source. The changeover is based on an adjustable outdoor temperature balance point setting that is determined by use of the included outdoor temperature sensor. The HPP is compatible with all 24 volt, hardwired, wireless or WiFi Thermostats, and can operate single and multistage heat pump and dual fuel systems using conventional single stage heating and cooling thermostats, without the need for heatpump thermostats.
Azeel Zoning Technology	HeatPump Pro	PAN-HP903	Y	N	N	
Azeel Zoning Technology	HeatPump Pro	PAN-HP904	Y	N	N	
Bosch	24V Interface	BMS-DRY-XXX	Y	Y	Y*	Requires one 24V Interface Kit, One Third Party Thermostat and double pole double throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the thermostat selected.
Bosch Thermotechnology Corp.	BoschConnectControl BCC110 Thermostat	BCC110	Y	N	Y	The BCC110 is an Energy Star certified smart thermostat. It is compatible with most HVAC applications. It is able to control dual fuel applications where heat pump is setup as primary and fossil fuel as a secondary based on outdoor ambient temperature (OAT). The OAT is received from an API that provides the temperature from the closest weather station to the zipcode provided by the user.
Bryant	24V Interface	KSAC0301230	Y	Y	Y*	Requires one 24V Interface Kit, one Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi enabled based on thermostat selected.
Bryant	24V Interface	KSAC0601230	Y	Y	Y*	Ductless 24V Interface Mini-Auxiliary Heat Source Support or On/Off - 12V connection option via CN3 port on the 24V interface; 12V output powered by the indoor unit main board 24V Installation Package: T1 Thermostat included - with optional extension cable for purchase for flexible installation. Configurable Setup: Dial codes and DIP switches (SW) for precision system adjustments. Power Requirements: Requires external 24V transformer input (not included). Simplified Wiring: Indoor-only wiring to the 24V interface; no outdoor connection required. *Wi-Fi Ready - Wireless functionality available depending on third-party thermostat selection
Bryant	Bryant Smart Thermostat	T51ATCCWF-01	Y	Y	Y	
Bryant	Wi-Fi Programmable Controller	KSACN1401AAA	No	Yes	Yes	Wi-Fi & App Control (Wired Programmable Controller) for Ductless Indoor Units/Ductless AHUs/Crossover AHUs - Heat Pump Control
Bryant	24V Interface Gen 3	KSAC0501230	Yes	Yes	Yes	Ductless 24V Interface Gen 3: 24V Third-party thermostat/App integration, Water level switch (SV) output option, (Defrost, Dehumidification, Alarm/Remote control via Dry contacts) 24V Transformer included
Bryant	Wi-Fi Programmable Controller	KSACN1701BAA	Yes	Yes	Yes	Two-Wire or 24V Wire Connection, Wi-Fi & App-Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.

						Two-Wire or 24V Wire Connection, Wi-Fi & App Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation).
Bryant Carrier	Wi-Fi Programmable Controller Infinity User Interface	KSACN170124AA SYSTXCOTD01-C	Yes Y	Yes Y	Yes Y	Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.
Carrier	Infinity User Interface	SYSTXCWIC01-C	Y	Y	Y	
Carrier	24V Interface	KSACD302230	Y	Y	Y*	Requires one 24V Interface Kit, one Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the Thermostat selected.
Carrier	Infinity User Interface	SYSTXCOTD01-C	N	Y	Y	Available in black and white Uses outdoor sensor for outdoor temperature and changeover
Carrier	Infinity User Interface	SYSTXCOCF01-B	N	Y	Y	Available in black and white Uses outdoor sensor for outdoor temperature and changeover
Carrier	Infinity User Interface	SYSTXCWIC01-B	N	Y	Y	Available in black and white Uses outdoor sensor for outdoor temperature and changeover
Carrier	Infinity User Interface	SYSTXCWIC01-C	N	Y	Y	Available in black and white Uses outdoor sensor for outdoor temperature and changeover
Carrier	Infinity User Interface	SYSTXCWIF01-B	N	Y	Y	Available in black and white Uses outdoor sensor for outdoor temperature and changeover
Carrier	Ecobee3.0 for Carrier Smart Therm	EB-STATE3LTCR-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Carrier	Ecobee3.0 for Carrier Smart Therm	EB-STATE3LTCR-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Carrier	Ecobee for Carrier Smart Thermostat	EB-STATE7LTCR-01	Y	N	Y	Uses local weather for outdoor temperature and change over
Carrier	Ecobee for Carrier Smart Thermostat	EB-STATE6LTCR-01	Y	N	Y	Uses local weather for outdoor temperature and change over

Carrier	Carrier Smart Thermostat	TSTATCEWF-01	Y	N	Y*	Uses local weather for outdoor temperature and change over
Carrier	24V Interface	KSAC050230	Y	Y	Y*	<u>Ductless 24V Interface Mini</u> - Auxiliary Heat Source Support or On/Off - 12V connection option via CR3 port on the 24V interface; 12V output powered by the indoor unit main board <u>24V Installation Package</u> - T1 Thermostat included with optional extension cable for purchase for flexible installation. Configurable Setup: Dial codes and DIP switches (SW) for precise system adjustments <u>Power Requirements</u> - Requires external 24V transformer input (not included). Simplified Wiring: Indoor-only wiring to the 24V interface; no outdoor connection required <u>Wi-Fi Ready</u> - Wireless functionality available depending on third-party thermostat selection
Carrier	Wi-Fi Programmable Controller	KSACN1401AAA	No	Yes	Yes	Wi-Fi & App Control (Wired Programmable Controller) for Ductless Indoor Units/Ductless AHUs/Crossover AHUs - Heat Pump Control
Carrier	24V Interface Gen 3	KSAC050230	Yes	Yes	Yes	Ductless 24V Interface Gen 3 24V Third-party thermostat/App integration, Water level switch (SV) output option, (Difrost, Dehumidification, Alarm/Remote control via Dry contacts) 24V Transformer included  Two-Wire or 24V Wire Connection, Wi-Fi & App Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation).
Carrier	Wi-Fi Programmable Controller	KSACN1701BAA	Yes	Yes	Yes	Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.  Two-Wire or 24V Wire Connection, Wi-Fi & App Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation).
Carrier Cielo WGL® Inc.	Wi-Fi Programmable Controller Cielo Breez Max (Smart AC controller for any brand ductless systems)	KSACN1701AAA BM102WA (Black Color Variant)	Yes Y	Yes N	Yes Y	Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface. The integrated control solution is based on Cielo's AWS Cloud platform called "Cielo Link®". It requires a Cielo Breez MAX smart AC controller (for ductless systems) and a Cielo Smart Thermostat for the conventional HVAC system (2H, 2C). No extra hardware or wiring is needed. Both Cielo Breez MAX and Cielo Smart Thermostat are connected through Cielo Link® (cloud platform). Cielo Home App is required to link the devices. Cielo Breez MAX can be powered through a 5V adapter or can be hardwired to 24V. Cielo Smart Thermostat is powered through standard 24V wiring. Cielo Link® enables the interplay of connected ductless systems and conventional ducted HVAC system. After powering up the Cielo Breez MAX and Cielo Smart Thermostat, the setup of integrated control is super easy through Cielo Home App.
Cielo WGL® Inc.	Cielo Breez Max (Smart AC controller for any brand ductless systems)	BM102WA (White Color Variant)	Y	N	Y	The integrated control solution is based on Cielo's AWS Cloud platform called "Cielo Link®". It requires a Cielo Breez MAX smart AC controller (for ductless systems) and a Cielo Smart Thermostat for the conventional HVAC system (2H, 2C). No extra hardware or wiring is needed. Both Cielo Breez MAX and Cielo Smart Thermostat are connected through Cielo Link® (cloud platform). Cielo Home App is required to link the devices. Cielo Breez MAX can be powered through a 5V adapter or can be hardwired to 24V. Cielo Smart Thermostat is powered through standard 24V wiring. Cielo Link® enables the interplay of connected ductless systems and conventional ducted HVAC system. After powering up the Cielo Breez MAX and Cielo Smart Thermostat, the setup of integrated control is super easy through Cielo Home App.
Cielo WGL® Inc.	Cielo Smart Thermostat ECO	TE101WA (White Color Variant)	Y	N	Y	Cielo Smart Thermostat Eco supports Conventional Systems for up to 2 stages of Heating & 2 stages of Cooling. For Heat Pumps it supports up to 4 Stages of Heating and 2 Stages of Cooling. Cielo Smart Thermostat Eco fetches outdoor temperature data from cloud and makes decisions based on that data for switching between Heat Pump and A/w heat source (furnace systems). In addition, the Cielo Smart Thermostat Eco can also be linked to Cielo Breez Max and/or Cielo Breez PLUS (Cielo's smart thermostat for mini splits) using Cielo Link® (our cloud based platform to switch between fossil fuel based systems and mini splits). Cielo Smart Thermostat Eco stores projected temperature data for next 72 hours to ensure its smooth decision-making process even if the Wi-Fi is temporarily lost. The product is available in Black and White Color variants.
Cielo WGL® Inc.	Cielo Smart Thermostat ECO	TE102WA (Black Color Variant)	Y	N	Y	Cielo Smart Thermostat Eco supports Conventional Systems for up to 2 stages of Heating & 2 stages of Cooling. For Heat Pumps it supports up to 4 Stages of Heating and 2 Stages of Cooling. Cielo Smart Thermostat Eco fetches outdoor temperature data from cloud and makes decisions based on that data for switching between Heat Pump and A/w heat source (furnace systems). In addition, the Cielo Smart Thermostat Eco can also be linked to Cielo Breez Max and/or Cielo Breez PLUS (Cielo's smart thermostat for mini splits) using Cielo Link® (our cloud based platform to switch between fossil fuel based systems and mini splits). Cielo Smart Thermostat Eco stores projected temperature data for next 72 hours to ensure its smooth decision-making process even if the Wi-Fi is temporarily lost. The product is available in Black and White Color variants.
Cielo WGL® Inc.	Cielo Breez Edge Pro	ED101WA	Yes	No	Yes	The integrated control solution is based on Cielo's AWS Cloud platform called "Cielo Link®". It requires a Cielo Breez Edge Pro smart AC controller (for ductless systems) and a Cielo Smart Thermostat for the conventional HVAC system (2H, 2C). No extra hardware or wiring is needed. Both Cielo Breez Edge Pro and Cielo Smart Thermostat are connected through Cielo Link® (cloud platform). Cielo Home App is required to link the devices. Cielo Breez Edge Pro can be powered through a 5V adapter or can be hardwired to 24V. Cielo Smart Thermostat is powered through standard 24V wiring. Cielo Link® enables the interplay of connected ductless systems and conventional ducted HVAC system. After powering up the Cielo Breez Edge Pro and Cielo Smart Thermostat, the setup of integrated control is super easy through Cielo Home App.
OMNA (CF-MIDEA)	24V Interface	KSACD40230	Y	Y	Y*	Requires one 24V Interface Kit, one Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the Thermostat selected.
Cooper&Hunter	IFTT	WiFi Module CH-WF02M & Smartest	N	Y	Y	IFTT App connects Cooper&Hunter with IFTT through C&H web remote app. Current IFTT compatible thermostats (for additional heat source) include EcoSense, and Honeywell as of 11/17/20. For list of devices, go to www.iftt.com/service/Environment-Control-&Monitoring. Integration is possible by linking compatible thermostat for additional heat source and Cooper&Hunter web remote app for Cooper&Hunter system into IFTT, then creating applet allowing IFTT to adjust primary and secondary heating systems, based on outdoor temperature.

Daikin	One+ (Replaces ENVI)	DTST-ONE ADA-A (Replaces DACA-TS-1)	Y	Y	Y	Compatible with Daikin Mini-Split and Multi Split Heat Pump Products. Thermostat is provided with communication adaptor that requires 110-240 VAC power supply. Additional adaptor (KOP9R032F) required for connection to FTX_NW3U indoor units.
Daikin	Daikin One Lite Connected Thermostat	DTST-LTE-LA-A	N	Y	Y	Compatible with most Daikin brand mini and multi split systems, see www.daikinone.com for specific details
Daikin	Daikin One Touch Smart Thermostat	DTST-TOU-A	N	Y	Y	Compatible with all Daikin brand communicating equipment
Daikin (Airzone)	DKN Plus Interface	AZABWSPDK	N	Y	Y	Compatible with Daikin Mini Splits and Daikin VRV indoor unit and allows integration of any thermostat to control the indoor unit operation. Can provide full integration via cloud API, Modbus or BACnet MSTP to control and monitor the indoor unit operation
Durastar	24V Interface	DR24VINT1	Y	Y	Y	Requires one 24V Interface Kit, One Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the thermostat selected.
EMERSON	SENGI	ST55	Y	N	Y	Switch over based on weather data associated with zipcode during set up <a href="https://sensicopeland.com/en-us/shop/sensi-sku-st55">https://sensicopeland.com/en-us/shop/sensi-sku-st55</a>
EWC Controls	Ultra-Zone	BMPus 3000	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
EWC Controls	Ultra-Zone	BMPus 5000	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
EWC Controls	Ultra-Zone	BMPus 7000	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
EWC Controls	Ultra-Zone	LDC-6	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
EWC Controls	Ultra-Zone	LDC-4	Y	Y	Y*	*With WiFi capable thermostat. Zone control for Centrally Ducted Heat Pump systems
Flair	Flair Bridge Pro	FLAIRBR02001P	Y	N	Y	Requires one Bridge Pro which is compatible with all brands of boilers and electric baseboard heating and communicates through our onboard radio frequency with the Flair Puck Pro (FLAIRPUCK002P) controlling each mini split head unit to accomplish integrated controls.
Flair	Puck 2 Pro	FLAIRPUCK002P	N	N	Y	One Flair Puck Pro is required for each mini split head unit and the Flair app must be digitally integrated with one of the following thermostats to accomplish integrated controls. Honeywell: All models of their smart wifi enabled thermostats that work with the Honeywell Home and Total Home Connect Apps. ecobee: All models of their smart wifi enabled thermostats that work with the ecobee app. Nest: All models of their smart wifi enabled thermostats that work with the Google Home app. Sensi: All models of their smart wifi enabled thermostats.

Fair	Puck Pro	FLAIRPUCK01P	N	N	Y	<p>Compatible Mini Split Brands and Compatible Smart Thermostats Listed at: <a href="http://fair.co/integrated-controls">fair.co/integrated-controls</a>. One Fair Puck Pro is required for each mini split head unit and the Fair app must be digitally integrated with one of the following thermostats to accomplish integrated controls.</p> <p>Honeywell: All models of their smart wifi enabled thermostats that work with the Honeywell Home and Total Home Connect Apps. ecobee: All models of their smart wifi enabled thermostats that work with the ecobee app. Nest: All models of their smart wifi enabled thermostats that work with the Google Home app.</p>	<a href="http://fair.co/integrated-controls">Fair.co/Integrated-controls</a>
Fujitsu	Wired Remote Controller (Touch Panel)	UTY-RNRJ2*	N	Y	N	<p>1 Series &amp; RGLX only - The existing heat source is energized to be operated through a 3rd party control circuit, via a 12 VDC external output signal from the indoor unit RC board. Primary Heat lockout or secondary heat lockout based on outdoor temperature is available.</p>	
Fujitsu	Wired or Wireless Remote Controller	Various	N	Y	N	<p>See instructions for compatible equipment. The alternate heat source is operated through a 3rd party control circuit, via a 12 VDC external output signal from the indoor unit PC board. Primary heat lockout or secondary heat lockout based on outdoor temperature is available.</p>	<a href="#">Fujitsu General Remote Controllers (7 types)</a>  <a href="#">Fujitsu General - Integrated Heating Control (Remote Controller) - Instructions</a>
Fujitsu	N2000 (Replaces Novus N2000)	8200-0001-30	N	N	N	<p>*Former controller Novus N2000* N2000 is the replacement series controller recommended by Fujitsu to be used with AirZage or Halcyon Mini-Split Heat Pump System. N2000 senses outside temperature and closes the control contact when the outside temp is about the set temp. When closed, this contact will enable the Halcyon to heat or cool based on the temp setting of the Halcyon System; when this contact is open, it will enable the Heat Pump from working. The installation requires both a wiring kit and external control board supplied by Fujitsu to be added to the inside unit. **Replaces 8200011300</p>	<a href="#">N2000 N2000 Temperature Controller - Operation Manual</a>  <a href="#">N2000 N2000 Temperature Controller - Operation Manual</a>
Fujitsu	Thermostat Converter	UTY-TTRX	Y	N	N	<p>Required installation includes a Thermostat Converter and 24 volt transformer (one UTY-TTRX can connect up to 16 indoor units), plus a dual fuel thermostat from OPL. Best as IC solution for single head, multihead, or air handler installations. Dual Fuel thermostat replaces existing central heat thermostat. Indoor units connected to each submeter (plus dual fuel thermostat) act as Single Zone. Fujitsu General - Integrated Heating Control (3rd Party Thermostat) - Instructions Third Party Thermostat Interface UTY-TTRX21 - Installation Manual</p>	<a href="#">Fujitsu General - Integrated Heating Control (3rd Party Thermostat) - Instructions</a>  <a href="#">Third Party Thermostat Interface UTY-TTRX21 - Installation Manual</a>
Fujitsu	WiFi Thermostat	Various	Y	Y	Y	<p>Honeywell Wi-Fi thermostat compatible with Gas, Electric and Oil on forced air, and radiant boilers</p>	
Fujitsu	WiFi Interface (UART)	UTY-TFSX1	N	Y	Y	<p>IFTTT solution combining any of the (3) WiFi Interface Modules listed at left, a Honeywell dual-stage Wi-Fi thermostat with IFTTT capability, used to control the existing heat source, and the IFTTT App. Access to Fujitsu IFTTT installation instructions are available via the below link upon establishing a Fujitsu account: Fujitsu General - Integrated Heating Control (IFTT) - Instructions</p>	<a href="#">Fujitsu General - Integrated Heating Control (IFTT) - Instructions</a>
Fujitsu	WiFi Interface (2-Wire Indoor Units)	UTY-TFSX2	N	Y	Y	<p><a href="#">2-Wire WiFi Module UTY-TFSX2 - Setting Manual</a></p>	
Fujitsu	Auxiliary Heating Output (NON-Wall mounted indoor units)	UTY-WXKXG	No	Yes	No	<p><a href="#">Because of external output "Aux Heater" the heat pump system can be programmed to disengage heat pump operation based on outdoor temperature and engage the "Aux Heater" contact to call on a secondary heating source. Programming is performed in the contractor menu "Function settings" and uses the built-in outdoor temperature sensor located at the outdoor unit. Outdoor signal is 12Vdc and will need to be isolated with a third-party relay (commonly BSA J11 for example) UTY-WXKXG output wiring will connect to the coil of the relay to close the normally open contact which engages existing 24 secondary heating source.</a>   <a href="#">UTY-WXKXG is compatible with all Fujitsu NON-Wall Mounted Indoor Units.</a></p>	
Fujitsu	Auxiliary Heating Output (Wall mounted indoor units)	UTY-WXKX5	No	Yes	No	<p><a href="#">Because of external output "Aux Heater" the heat pump system can be programmed to disengage heat pump operation based on outdoor temperature and engage the "Aux Heater" contact to call on a secondary heating source. Programming is performed in the contractor menu "Function settings" and uses the built-in outdoor temperature sensor located at the outdoor unit. Outdoor signal is 12Vdc and will need to be isolated with a third-party relay (commonly BSA J11 for example) UTY-WXKX5 output wiring will connect to the coil of the relay to close the normally open contact which engages existing 24 secondary heating source.</a>   <a href="#">UTY-WXKX5 is compatible with all Fujitsu Wall Mounted Indoor Units.</a></p>	
Google Nest	Nest Thermostat E	T40085	Y	N	Y		
Google Nest	Nest Thermostat E	T40015	Y	N	Y		
Google Nest	Nest Thermostat E	T40025	Y	N	Y		

Google Nest	Google Nest Thermostat	GAG3000-US	Y	N	Y	
Google Nest	Nest Learning Thermostat 3rd Gen	T3D18US	Y	N	Y	
Google Nest	Nest Learning Thermostat 3rd Gen	T3D19US	Y	N	Y	
Google Nest	Nest Learning Thermostat 3rd Gen	T3D32US	Y	N	Y	
Gree	WK-G1DWC1	NC20700410	Y	Y	Y	The WK-G1DWC1 thermostat supports communication exclusively with Gree Flex indoor and outdoor units via RS485 protocol. Integrated control requires the Gree+ App, which ensures a seamless setup process after powering up.
Gree	Honeywell TG Pro Smart	THE320WF-2003	Y	N	Y	Requires Honeywell TG Pro Smart (THE320WF-2003) WiFi thermostat that turns on the secondary heat source at 40° and "Set Point" Programmable Flair Gateway (1.15x) WiFi 2.4GHz Puck that will ensure the Gree mini split heat pump will be on when thermostat turns off the secondary heat. Appropriate WiFi accessibility is provided by the homeowner and not included in this package. Requires Flair Puck -ICD001P
Haier	#TTT	QAWF01A	N	Y	Y	Requires Ecobee Thermostat integration with Haier WiFi via iFTTT Applet. Proper understanding and installation of the Ecobee thermostat is a prerequisite.
Hisense (Arizona)	Aidoo Pro	AZ46W5PHS1	N	Y	Y	Compatible with all ducted and non-ducted units using the CN-WRED/CN18 terminal. It can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the Aidoo Pro can be used on its own for the integrated control as it has a Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native Mitsubishi controls, switchover can be done based off of outdoor temperature through the app.
ICP	24V Interface	KSACD301230	Y	Y	Y*	Requires one 24V Interface Kit, one Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *WiFi enabled based on thermostat selected.
ICP	24V Interface	KSACD601230	Y	Y	Y*	Ductless 24V Interface Mini: Auxiliary Heat Source Support or On/Off - 12V connection option via CH3 port on the 24V interface; 12V output powered by the indoor unit main board 24V Installation Package: T1 Thermistor included- with optional extension cable for purchase for flexible installation. Configurable Setup: Dial codes and DIP switches (SW) for precise system adjustments Power Requirements: Requires external 24V transformer input (not included). Simplified Wiring: Indoor only wiring to the 24V interface; no outdoor connection required. *Wi-Fi Ready - Wireless functionality available depending on third party thermostat selection
ICP	Wi-Fi Programmable Controller	KSACN1401AAA	No	Yes	Yes	Wi-Fi & App Control (Wired Programmable Controller) for Ductless Indoor Units/Ductless AHUs/Crossover AHUs - Heat Pump Control
ICP	24V Interface Gen 3	KSACD501230	Yes	Yes	Yes	Ductless 24V Interface Gen 3: 24V Third-party thermostat/App integration, Water level switch (SV) output option, (De) frost, Dehumidification, Alarm/Remote control via Dry contacts) 24V Transformer included
ICP	Wi-Fi Programmable Controller	KSACN1701BAA	Yes	Yes	Yes	Two-Wire or 24V Wire Connection, Wi-Fi & App-Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.

			Two-Wire or 24V Wire Connection, Wi-Fi & App Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard Installation).			
ICP Innovair Solutions	Wi-Fi Programmable Controller SLIM4 Control	KSACN1701A4A 17317100009536	Yes N	Yes Y	Yes Y	Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.
Innovair Solutions USA Ion	SLIM Smart Thermostat Ion Black	SLIMST900X SYST0101CW	Yes N	Yes Y	Yes Y	This thermostat has both protocols, 24V and communicating. Units local weather for outdoor temperature and change over
Ion	Ion Black	SYST0201CW	N	Y	Y	Units local weather for outdoor temperature and change over
Lennox	CDRE	LHT***H	Y	Y	N	Lennox CDRE Controller is the on board unitary controller for Lennox High Efficiency packaged Heat Pump and Dual Fuel Models (LHT***H / LDT***H). Unitary controller operates heating and cooling based on inputs from 24v thermostat, communicating room sensor, or Building Automation system. Primary heating method is heat pump with secondary heating source as (optional) electric heat or backup gas heat. Balance point determines the temperature at which heating source changes to secondary, and is selectable onboard the unitary controller.
Lennox	CDRE	LDT***H	Y	Y	N	Lennox CDRE Controller is the on board unitary controller for Lennox High Efficiency packaged Heat Pump and Dual Fuel Models (LHT***H / LDT***H). Unitary controller operates heating and cooling based on inputs from 24v thermostat, communicating room sensor, or Building Automation system. Primary heating method is heat pump with secondary heating source as (optional) electric heat or backup gas heat. Balance point determines the temperature at which heating source changes to secondary, and is selectable onboard the unitary controller.
Lennox Industries Inc.	CS8500 Communicating Sensor	24K53	Y	Y	N	Communicating 4 Heat/4 Cool
Lennox Industries Inc.	CS8500 Communicating Sensor	24K55	Y	Y	N	Communicating 4 Heat/4 Cool
Lennox Industries Inc.	CS7500 Commercial Thermostat	24K41	Y	N	N	Universal 4 Heat/3 Cool
LG Electronics	Auxiliary Heat Relay Kit	PRABH1	Y	Y	N	
LG Electronics	Aux Heater Kit Highwall Multi	PRAB51	Y	Y	N	LG Option 2: Wall Units Multi-Zone 16u Aux Hr Relay PrAB51 (1 Per 16U)
LG Electronics	Aux Heater Kit All Ducted/Cassette	PRABH0	Y	Y	N	LG Option 3: Aux Hr Relay PrABH0 Ducted, Cassette 16u (1 Per 16U)

LG Electronics	A Series Idu Model - Dry Contact Built In	ALL "A" SERIES IDU	Y	Y	Y	LG Option 5: Arnu Series IDU + 2 Stage Tstat With Wired/Wireless/Internet Odt Sensing Wired Through Relay To Cn-Ext Of Any (1) IDU
LG Electronics	Thermostat	PREMTB811	Y	Y	Y	Standard Controller with Black Case
LG Electronics	Thermostat	PREMTB101	Y	Y	Y	Standard Controller with White Case
LG MFG	Thermostat	PREMT000	Y	Y	N	Simple Thermostat
LG MFG	Dry Contact	FORC8320	Y	N	N	Dry contact for third party t-stat
Mitsubishi Electric	Mitsubishi PAC-US445CN-1 - Thermostat Adapter Interface	PAC-US445-CN-1	Y	Y*	N	Must provide 3rd party 2 stage thermostat and 24V transformer.
Mitsubishi Electric	Intelli-Heat	PAA Series	Y	Y	N	PAA-series (PAA-BA3BNL, PAA-AA3ENL, PAA-AA3ANL, PAA-BA2BNL, PAA-BA3BNL, PAA-AA3BNL, PAA-CA3ENL, PAA-BA3ENL, PAA-BA42NL, PAA-CA42NL) Indoor units are compatible with P-Series Outdoor units and MXZ Outdoor Units. Please review approved submittals on Mitsubishi.com or use Diamond System Builder software to determine specific applications and capacities.
Mitsubishi Electric	Kumo Station	PAC-WHS01HC-E	N	N	Y	Requires an outdoor temperature sensor and each unit needs a Kumo Cloud interface Required outdoor temperature sensor and each unit needs a Kumo Cloud interface - C708BU1006/U Required Kumo Cloud interface for each outdoor unit. - PAC-USW5002-WF-2
Mitsubishi Electric	Thermostat Interface	PAC-US444CN-1	Y	Y*	Y*	Requires a T-Stat interface and transformer for each indoor unit, and a 2 stage thermostat by any manufacturer. ACTS AS IC WITH Q/I LISTED THERMOSTAT. To operate the indoor unit via Thermostat interface (PAC-US444CN-1) using a 24VAC thermostat in the heat pump configuration (using Q/I with Y1 & Y2 output) requires a double pole-double throw relay, see Application Note 3044. *Depends on Thermostat Selected. **Requires Transformer VRL24-210
Mitsubishi Electric	Thermostat Interface	PAC-US445CN-1	Y	Y*	Y*	Requires a T-Stat interface and transformer for each indoor unit, and a 2 stage thermostat by any manufacturer. ACTS AS IC WITH Q/I LISTED THERMOSTAT. To operate the indoor unit via Thermostat interface (PAC-US445CN-1) using a 24VAC thermostat in the heat pump configuration (using Q/I with Y1 & Y2 output) requires a double pole-double throw relay, see Application Note 3044. *Depends on Thermostat Selected. **Requires Transformer VRL24-210
Mitsubishi Electric	Kumo Cloud	PAC-USW5002-WF-2	N	Y	Y	
Mitsubishi Electric	CH24 Relay Kit and compatible indoor units	CH24RELAY-KIT-CMS	Y	N	N	Install CH24 relay kit in parallel with or without back-up heat thermostat to activate second stage on drop temperature. Outdoor balance point temperature can be set for CH24 activation on models with handheld control. Above high set temperature, only heat pump operation is available. When outdoor temperature is below balance point temperature setting, back-up heat is available when indoor temperature drops 2°F below set point. Back-up heat will operate until indoor temperature reaches set point temperature of heat pump; heat pump continues to operate throughout. Compatible indoor units include Wall Mounted MSZ-FS Series, Floor Mounted MFZ-KJ Series, Ceiling Cassettes MSZ-SLZ & MSZ-MUZ, Ducted units SVZ, PVA, SEZ, PEAD series products.
Mitsubishi Electric	PAA-41MAU Deluxe MA Remote Controller	PAA-41MAU	N	Y	N	Use in conjunction with CH24 relay kit (CH24RELAY-KIT-CMS). - Select the outdoor air temperature at which backup heater operation will be enabled and disabled: enable on rise, disable on fall. - Select the outdoor air temperature at which backup heater operation will be enabled and disabled: enable on fall, disable on rise. <a href="https://mylinkdrive.com/viewPdf?url=Http://s3.amazonaws.com/enter.mehvac.com/DAMRoot/Original/10007/M_S205submit_PAA-41MAU.pdf">https://mylinkdrive.com/viewPdf?url=Http://s3.amazonaws.com/enter.mehvac.com/DAMRoot/Original/10007/M_S205submit_PAA-41MAU.pdf</a>
						<a href="http://doc.airzonecloud.com/Documentation/A26/A66/PT_A26WSPANEL_MUL.pdf">http://doc.airzonecloud.com/Documentation/A26/A66/PT_A26WSPANEL_MUL.pdf</a>

Mitsubishi Electric	Airzone	AZB5R2MEL	N	Y	Y	Compatible with Mitsubishi M-Series, P-Series, & S-Series indoor units. Provides means of controlling any heating and cooling source equipment and specifying sequence of stages as well as differential temperature for activation of secondary sources. WiFi & BACnet functionality optional.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A18AA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A18BA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A24AA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A24BA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A30AA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A30BA	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A36BA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A36CA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A42BA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Intelli-HEAT Casad Cool	PA4-A42CA1	Y	N	N	Compatible with any thermostatically controlled ANSI/221.47/CSA2.3 certified furnaces natural gas or propane furnace. Multiple balance point settings for heat pump and furnace operation to ensure sustainable and cost-effective heating (-11°F, 9°F, 14°F, 19°F, 23°F, 32°F, Furnace only). Intelligent Comfort Control function ensures homeowner comfort independent of balance point setting.
Mitsubishi Electric	Ecodan	ERS-NMGE	N	N	N	
MRCOOL, LLC	MRCOOL Smart Wi-Fi Mini-Stat	MST05	Y	N	Y	The integrated control solution leverages our AWS Cloud platform, known as "MRCOOL Link". This system requires the MRCOOL Smart Wi-Fi Mini-Stat (for MRCOOL equipment) and the MRCOOL Smart Thermostat for traditional ducted HVAC systems (THVCL). No additional hardware or wiring is necessary. Both the MRCOOL Smart Wi-Fi Mini-Stat and the MRCOOL Smart Thermostat connect via the MRCOOL Link cloud platform using the "MRCOOL SmartHVAC" App. The MRCOOL SmartHVAC App is essential for linking the devices. The MRCOOL Smart Wi-Fi Mini-Stat can be powered with a 24V adapter or hardwired to 24V, while the MRCOOL Smart Thermostat operates on standard 24V wiring. This setup allows seamless integration between ductless and conventional ducted HVAC systems. Once powered, the MRCOOL Smart Wi-Fi Mini-Stat and MRCOOL Smart Thermostat are easily configured through the MRCOOL SmartHVAC App.

Panasonic	Honeywell LVRC	TH832WHF5002/U	Y	Y	Y	Fossil Fuel Total For Panasonic IC OPS Solution
Panasonic	Honeywell LVRC T6	TH6220WF2006	Y	Y	Y	Fossil Fuel Total For Panasonic IC OPS Solution
Panasonic	IFTT Connect	PCDF19	N	Y	N	IFTT App connects Honeywell DG integrated with a Panasonic mini-split and a Honeywell Lyric integrated with and auxiliary heat system. Installation contractors shall complete Panasonic training and be authorized to install Panasonic residential mini-split heat pumps.
Payne	24V interface	KSACD302230	Y	Y	Y*	Requires one 24V interface kit, one Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi enabled based on thermostat selected.
Payne	24V interface	KSACD602230	Y	Y	Y*	Ductless 24V Interface Mini: Auxiliary Heat Source Support or On/Off. 12V connection option via CN3 port on the 24V interface. 12V output powered by the indoor unit main board. 24V Installation Package: T1 Thermostat included with optional extension cable for purchase for flexible installation. Configurable Setup: Dial codes and DIP switches (SW) for precise system adjustments. Power Requirements: Requires external 24V transformer input (not included). Simplified Wiring: Indoor-only wiring to the 24V interface; no outdoor connection required. *Wi-Fi Ready - Wireless functionality available depending on third-party thermostat selection
Payne	Wi-Fi Programmable Controller	KSACN1401AAA	No	Yes	Yes	Wi-Fi App Control: (Wired Programmable Controller) for Ductless Indoor Units/Ductless AHUs/Crossover AHUs - Heat Pump Control
Payne	24V interface Gen 3	KSACD502230	Yes	Yes	Yes	Ductless 24V Interface Gen 3 24V Third-party thermostat/App integration, Water level switch (SV) output option, (De)humidification, Alarm/Remote control via Dry contacts) 24V Transformer included
Payne	Wi-Fi Programmable Controller	KSACN1701BAA	Yes	Yes	Yes	Two-Wire or 24V Wire Connection, Wi-Fi & App-Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface.
Payne Pioneer	Wi-Fi Programmable Controller 24V interface	KSACN1701AAA TST-24VIM-ECM45	Yes Y	Yes Y	Yes Y*	Two-Wire or 24V Wire Connection, Wi-Fi & App-Enabled, Wired Programmable Controller for Ductless Multi-Positional AHUs, Multi-Family AHUs, Crossover Multi-Positional AHUs, Crossover Coil, and Furnace Applications (Standard installation). Compatible with standard Ductless Indoor Units only when paired with a compatible 24V interface. Requires one 24V interface kit, one Third Party Thermostat and Double Pole Double Throw (DPDT) relay per indoor unit. *Wi-Fi Enabled based on the Thermostat selected.
Pioneer	IFTT	TST-APWHIMUSB TST-LCACWH9P	N	Y	Y	IFTT connects to the Wi-Fi enabled Pioneer split heat pump via the smartphone app, allowing for two-way communication between the mini-split and the main heat source. Then an IFTT applet can be created to allow for automatic changeover between the primary and secondary heat sources, based on the real-time outdoor temperature. The main heat source should be controlled via a Wi-Fi and IFTT compatible 3rd party thermostat, such as Nest, Ecobee, or Honeywell Home. For a full list, see <a href="https://iftt.com/explore/services">https://iftt.com/explore/services</a>
Pioneer (Arizona)	Aidoo Pro	PACABWSP01	N	Y	Y	The Arizona Aidoo Pro is compatible with all Pioneer ducted and non-ducted units that have X-Y-E wiring. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can be done through the thermostat, or the Aidoo Pro can be used on its own for the integrated control as it has an Aux Heat relay output. If using the thermostat, switchover can be done through the thermostat logic. If using the Aidoo Pro with native controls, switchover can be done based off of the current outdoor temperature through the app.
P101	7555	7755	Y	N	N	Requires a R250i Wired Outdoor Sensor. Dual Fuel Balance Point can be set in the options.

Pro1	B55sh	T855sh	Y	N	N	Requires a R250s Wired Outdoor Sensor. Dual Fuel Balance Point can be set in the options.
Pro1	B55sh	T855sh	Y	N	Y	Requires a R250s Wired Outdoor Sensor. Dual Fuel Balance Point can be set in the options.
Pro1	Profsync	T755WHO	Y	N	N	Requires a R250W Wireless Outdoor Sensor. Dual Fuel Balance Point can be set in the options
Resideo Technology Inc. under the Honeywell Home Brand	D6 Pro Wi-Fi Ductless Controller	DC6000WF1001/U	N	N	Y	This solution is cloud-based, and utilizes a D6 controller with the Mini-Split and a T Series Wi-Fi thermostat on the conventional HVAC system. This would be at a 1:1 relationship. There are no other devices needed other than the two thermostats. There is no additional wiring needed. A simple to use feature, curated and available in the Honeywell Home Thermostat App, pairs the two devices in minutes and the cloud algorithm takes over from there. The D6 Controller will work with the Honeywell Home T5, T5+, T6, T9 and T10, demand response capable, smart thermostat line. These models include: RCHT812WF2005/U or W; RCHT812WF2006/U or W; RCHT812WF192003/U or W; RCHT812WF192002/U or W; RCHT812WF192001/U or W; TH6220WF2006/U and TH6320WF2003/U. The D6 Controller and T-Series Thermostats can be found at the Resideo.com website for more information. (The D6 Controller is powered by 120V - it plugs into a standard wall outlet)
Rheem	Econet Smart Thermostat	RHT800YS	Y	Y	Y	For use with Rheem communicating equipment only.
Samsung	DMS 2.5 Data Management Server	MIM-DDLAUN	N	Y	N	The Samsung DMS 2.5 Data Management Server Model MIM-DDLAUN has the capability to enable/disable Samsung heat pumps and external heat sources through a programmable logic function and onboard digital output terminals. Sequence: • The DMS 2.5 will monitor the outdoor temperature sensor of the Samsung outdoor heat pump unit. • When the outdoor temperature falls below the programmed setting, the Samsung indoor units will be commanded off and the alternate fossil fuel heat source will be enabled. Enabling is done through one of the 8 on board digital outputs that provide 24VDC. A normally open relay with a 24VDC coil is required. • Once enabled, the fossil fuel source will maintain the room temperature through its independent control. The enable/disable output will interrupt the heating control until outdoor temperature is below the programmed setting.
Samsung HVAC	Thermostat Adaptor	MIM-A60UN	Y	N	N	Requires 1.5 ton adaptor (maximum 2 indoor units per adaptor), 24VAC transformer, and dual fuel thermostat by any manufacturer <a href="https://www.smarthings.com/products/518">https://www.smarthings.com/products/518</a> <a href="https://www.samsunghvac.com/products">https://www.samsunghvac.com/products</a>
Samsung HVAC	Samsung Wi-Fi Adaptor	MIM-H04UN	N	Y	Y	Compatible with all Samsung DVMs, single zone CAC systems, FMM systems with Ducted, Cassette, and/or Console units connected. Once the WiFi adaptor is installed the Smart Things App controls up to 16 indoor units simultaneously and the balance point changer of the Honeywell thermostat. The following thermostats are required for the migration of secondary heat source. Honeywell: TH6220WF2006/U, TH6220WF2006/U, TH6221WF1001/U, TH9320WF5005/U. All Samsung residential send free wall units already have WiFi adaptor pre-installed and would just require one of the listed thermostats.
Samsung HVAC	SmartThings with SmartThings compatible Thermostat	All Samsung SmartThings-enabled Mini-splits, Heat Pumps, Cassettes, etc. See Notes for Models.	N	Y	Y	Samsung HVAC products using SmartThings App to connect to any of the following ST enabled thermostats from the following brands: Zigg, American Standard, Ecobee, Fibaro, Nest, Honeywell, Lux, Nexa, Popp, Snoop, Staipros, Trane, Zen. See link below for specific models. <a href="https://www.smarthings.com/products/518">https://www.smarthings.com/products/518</a> *Self-enabled Dual Fuel Thermostat must be listed on IC QPL. Integration is possible by adding compatible thermostat to SmartThings App and automating controls through the App. The following Samsung HVAC models support SmartThings: WindFree 2.0, WindFree 2.0e, Max Heat 2.0, Max, Quantum 2.0, Free Joint Multi, Slim Duct, Free Joint Multi Max Heat, WindFree Mini 4-way Cassette, Console, 360 Cassette, WindFree 4-way Cassette, Duct 5, Multi-Position Air Handler, High Wall, Light Commercial Outdoor Unit, Light Commercial Max Heat Outdoor Unit, WindFree 4-way Cassette Max Heat, Duct 5 Max Heat, Multi-Position Air Handler Max Heat, mixed low Ambient Cooling, DVM S Eco, DVM S Water, ISE Duct, OMP Duct, Big Ceiling, Under Ceiling, Floor Standing, 30, DVM S Max Heat. See link below for specific model numbers. The Airzone Aidoo Pro is compatible with all ducted and non-ducted units that have F2 and F4 communication terminals. The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the Aidoo Pro can be used on its own for the integrated control as it has a Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native Samsung controls, switchover can be done based off of outdoor temperature through the app.
Samsung HVAC (Airzone)	Aidoo Pro	AZ40WFS5A2	N	Y	Y	The Aidoo Pro can be used with any 3rd party thermostat and the integrated control can be done through the thermostat or the Aidoo Pro can be used on its own for the integrated control as it has a Aux heat relay output. If using the thermostat, switchover can be done through the thermostat logic and if using the Aidoo Pro with native Samsung controls, switchover can be done based off of outdoor temperature through the app.
Trane	Symbio 700	X45091784001	Y	Y	Y	
Venstar	Explorer Mini	T2000	Yes	No	Yes	
Venstar	ColorTouch	T7900	Yes	No	Yes	

Venstar	ColorTouch	T7850	Yes	No	Yes	
Venstar ZONEFIRST	Explorer 14Q Zone Control Panel	T3950-14Q H2	Yes Y	No N	Yes N	Two and Three Zone Control for Single and Two Stage/Speed Heat Pumps w/Dual Fuel and most all conventional and w-fi heat pump thermostats. Panel has multiple staging options: 1) from any zone thermostat, 2) adjustable timer on zone panel or 3) the percentage of zones calling. Less than 50%, first stage only, greater than 51% second stage. Dual fuel operation based on wired Outdoor Air Sensor (OAS) with adjustable temperature setting on zone panel.
ZONEFIRST	Zone Control Panel	H2P	Y	N	N	Two and Three Zone Control for Single and Two Stage/Speed Heat Pumps w/Dual Fuel and most all conventional and w-fi heat pump thermostats. Panel has multiple staging options: 1) from any zone thermostat, 2) adjustable timer on zone panel or 3) the percentage of zones calling. Less than 50%, first stage only, greater than 51% second stage. Dual fuel operation based on wired Outdoor Air Sensor (OAS) with adjustable temperature setting on zone panel.
ZONEFIRST	Zone Control Panel	MDP3	Y	N	N	Two and Three Zone Control Panel expandable to 100 Zones for Single and Two Stage/Speed Heat Pumps w/Dual Fuel and most all conventional and w-fi heat pump thermostats. Panel has multiple staging options: 1) from any zone thermostat, 2) adjustable timer on zone panel, 3) the percentage of zones calling. Less than 50%, first stage only, greater than 51% second stage. Staging and Dual fuel operation can also be based on wired Outdoor Air Sensor (OAS) with adjustable temperature setting on zone panel or the Leaving/Supply Air Sensor (LPS) also with adjustable temp setting on panel's menu driven display. Staging on supply air temp is a more advanced method for newer heat pumps with cold climate performance that can still deliver warm supply temps at lower outdoor temps, improving overall efficiency.
ZONEFIRST	BLISS Zone System	BZS	Y	Y	Y	Multi-Zone System with Integrated Combination Light Switch Thermostats (LST) for each zone for remote Wi-Fi control and monitoring of system operation. Heat Pump staging and Dual fuel changeover based on supply air sensors at each zone (WDS). Staging is set based on supply air temperatures rising and falling for both heating and cooling. When specific supply temp settings are not able to maintain the Bliss system stages and when needed will switch to dual fuel back-up for extreme temps. Remote monitoring and alerts can be sent when minimum system temps are not maintained.